

TPower I55 BIOS Manual

BIOS Setup	1
1 Main Menu.....	3
2 Advanced Menu.....	8
3 PCIPnP Menu.....	23
4 Boot Menu.....	26
5 Chipset Menu.....	29
6 O.N.EMenu.....	32
7 Exit Menu.....	45

TPower I55 BIOS Manual

BIOS Setup

Introduction

The purpose of this manual is to describe the settings in the AMI BIOS Setup program on this motherboard. The Setup program allows users to modify the basic system configuration and save these settings to CMOS RAM. The power of CMOS RAM is supplied by a battery so that it retains the Setup information when the power is turned off.

Basic Input-Output System (BIOS) determines what a computer can do without accessing programs from a disk. This system controls most of the input and output devices such as keyboard, mouse, serial ports and disk drives. BIOS activates at the first stage of the booting process, loading and executing the operating system. Some additional features, such as virus and password protection or chipset fine-tuning options are also included in BIOS.

The rest of this manual will guide you through the options and settings in BIOS Setup.

Plug and Play Support

This AMI BIOS supports the Plug and Play Version 1.0A specification.

EPA Green PC Support

This AMI BIOS supports Version 1.03 of the EPA Green PC specification.

APM Support

This AMI BIOS supports Version 1.1&1.2 of the Advanced Power Management (APM) specification. Power management features are implemented via the System Management Interrupt (SMI). Sleep and Suspend power management modes are supported. Power to the hard disk drives and video monitors can also be managed by this AMI BIOS.

ACPI Support

AMI ACPI BIOS support Version 1.0/2.0 of Advanced Configuration and Power interface specification (ACPI). It provides ASL code for power management and device configuration capabilities as defined in the ACPI specification, developed by Microsoft, Intel and Toshiba.

TPower I55 BIOS Manual

PCI Bus Support

This AMI BIOS also supports Version 2.3 of the Intel PCI (Peripheral Component Interconnect) local bus specification.

DRAM Support


DDR3 SDRAM (Double Data Rate III Synchronous DRAM) is supported.

Supported CPUs

This AMI BIOS supports the Intel CPU.

Using Setup

When starting up the computer, press **** during the **Power-On Self-Test (POST)** to enter the BIOS setup utility. In the BIOS setup utility, you will see **General Help** description at the top right corner, and this is providing a brief description of the selected item. **Navigation Keys** for that particular menu are at the bottom right corner, and you can use these keys to select item and change the settings.




Notice

- The default BIOS settings apply for most conditions to ensure optimum performance of the motherboard. If the system becomes unstable after changing any settings, please load the default settings to ensure system's compatibility and stability. Use Load Setup Default under the Exit Menu.
- For better system performance, the BIOS firmware is being continuously updated. The BIOS information described in this manual is for your reference only. The actual BIOS information and settings on board may be slightly different from this manual.
- The content of this manual is subject to be changed without notice. We will not be responsible for any mistakes found in this user's manual and any system damage that may be caused by wrong-settings.

TPower I55 BIOS Manual

1 Main Menu

Once you enter AMI BIOS Setup Utility, the Main Menu will appear on the screen providing an overview of the basic system information.



AMI BIOS

Shows system information including BIOS version, built date, etc.

System Memory

Shows system memory size, VGA shard memory will be excluded.

System Time

Set the system internal clock.

System Date

Set the system date. Note that the 'Day' automatically changes when you set the date.

Floppy A


Select the type of floppy disk drive installed in your system.

Options: 360K, 5.25 in / 1.2M, 5.25 in / 720K, 3.5 in / 1.44M, 3.5 in / 2.88M, 3.5 in / None

TPower I55 BIOS Manual

IDE/SATA Configuration

The BIOS will automatically detect the presence of IDE/SATA devices. There is a sub-menu for each IDE/SATA device. Select a device and press <Enter> to enter the sub-menu of detailed options.



Configure SATA as

This item allows you to choose the SATA operation mode.

Options: IDE (Default) / RAID / AHCI / Disabled

SATA#1 Configuration

This item allows you to control the onboard SATA controller.

Options: Compatible (Default) / Enhanced


SATA#2 Configuration

This item allows you to control the onboard SATA controller.

Options: Enhanced (Default) / Disabled

TPower I55 BIOS Manual


AHCI Configuration



AHCI BIOS Support

This BIOS feature controls the AHCI function of the SATA controller.
Options: Enabled (Default) / Disabled

AHCI Port0/Port1/Port2/Port3/Port4/Port5



TPower I55 BIOS Manual

Device

This area shows the detected connected device.

SATA Port0/1/2/3/4/5

This item allows you to select the connected device type.


Options: Auto (Default) / Not Installed

S.M.A.R.T.

This item allows you to control the device S.M.A.R.T function.

Options: Enabled (Default) / Disabled

SATA 1/2/3/4/5/6 Device; ESATA 1/2; Primary IDE Master/Slave



The BIOS detects the information and values of respective devices, and these information and values are shown below to the name of the sub-menu.

Type

Select the type of the IDE/SATA drive.

Options: Auto (Default) / CDROM / ARMD / Not Installed

LBA/Large Mode

Enable or disable the LBA mode.

Options: Auto (Default) / Disabled

Block (MultiSector Transfer)

Enable or disable multi-sector transfer.

Options: Auto (Default) / Disabled

TPower I55 BIOS Manual

PIO Mode

Select the PIO mode.

Options: Auto (Default) / 0 / 1 / 2 / 3 / 4

DMA Mode

Select the DMA mode.

Options: Auto (Default) / SWDMA0 ~ 2 / MWDMA0 ~ 2 / UDMA0 ~ 5

S.M.A.R.T

Set the Smart Monitoring, Analysis, and Reporting Technology.

Options: Auto (Default) / Disabled / Enabled

32Bit Data Transfer

Enable or disable 32-bit data transfer.

Options: Enabled (Default) / Disabled

Hot Plug

This item allows you to control the hot-plug function under RAID or AHCI mode.

Options: Disabled (Default) / Enabled

Hard Disk Write Protect

Disable or enable device write protection. This will be effective only if the device is accessed through BIOS.

Options: Disabled (Default) / Enabled

IDE Detect Time Out (Sec)

Select the time out value for detecting IDE/SATA devices.

Options: 35 (Default) / 30 / 25 / 20 / 15 / 10 / 5 / 0

ATA(PI) 80Pin Cable Detection

Select the mechanism for detecting 80Pin ATA(PI) Cable..

Options: Host & Device (Default) / Host / Device


TPower I55 BIOS Manual

2 Advanced Menu

The Advanced Menu allows you to configure the settings of CPU, Super I/O, Power Management, and other system devices.


Notice

- Beware of that setting inappropriate values in items of this menu may cause system to malfunction.



CPU Configuration

This item shows the CPU information that the BIOS automatically detects.



TPower I55 BIOS Manual

C1E Support

C1E is “Enhanced Halt State” function, this function helps to save power and decrease heat by lowering CPU frequency while the processor is not working.

Options: Enabled (Default) / Disabled

Hardware Prefetcher

The processor has a hardware prefetcher that automatically analyzes its requirements and prefetches data and instructions from the memory into the Level 2 cache that are likely to be required in the near future. This reduces the latency associated with memory reads.

Options: Enabled (Default) / Disabled

Adjacent Cache Line Prefetch

The processor has a hardware adjacent cache line prefetch mechanism that automatically fetches an extra 64-byte cache line whenever the processor requests for a 64-byte cache line. This reduces cache latency by making the next cache line immediately available if the processor requires it as well.

Options: Enabled (Default) / Disabled

Max CPUID Value Limit

When the computer is booted up, the operating system executes the CPUID instruction to identify the processor and its capabilities. Before it can do so, it must first query the processor to find out the highest input value CPUID recognizes. This determines the kind of basic information CPUID can provide the operating system.

Options: Disabled (Default) / Enabled

Intel(R) Virtualization Tech

Virtualization Technology can virtually separate your system resource into several parts, thus enhance the performance when running virtual machines or multi interface systems.

Options: Enabled (Default) / Disabled

CPU TM Function

The CPU TM Function is to throttle the clock speed of higher speed Prescott's to help keep them cool.

Options: Disabled (Default) / Enabled

TPower I55 BIOS Manual

Execute-Disable Bit Capability

This item allows you to configure the Execute Disabled Bit function, which protects your system from buffer overflow attacks.

Options: Enabled (Default) / Disabled

Intel (R) HT Technology

Hyper Threading Technology can improve performance by splitting instructions into multiple streams.

Options: Enabled (Default) / Disabled

Active Processor Cores


This item allows you to set the number of cores to enable in each processor package.

Options: All (Default) / 1 / 2

A20M

Options: Disabled (Default) / Enabled

SuperIO Configuration



TPower I55 BIOS Manual

Onboard Floppy Controller

Select enabled if your system has a floppy disk controller (FDC) installed on the system board and you wish to use it. If you installed another FDC or the system uses no floppy drive, select disabled in this field.

Options: Enabled (Default) / Disabled

Floppy Drive Swap

This item allows you swap floppy drive.

Options: Disabled (Default) / Enabled

Keyboard PowerOn

This item allows you to control the keyboard power on function.

Options: Disabled (Default) / Specific Key / Stroke Key

Specific Key Enter

This item will show only when Keyboard PowerOn is set “Specific Key.”

Stroke Keys Selected

This item will show only when Keyboard PowerOn is set “Stroke Key.”

Options: Ctrl+F1 (Default) / Wake Key / Power Key / Ctrl+F2 / Ctrl+F3 /
Ctrl +F4 / Ctrl+F5 / Ctrl+F6

Mouse PowerOn

This item allows you to control the mouse power on function.

Options: Disabled (Default) / Enabled

Restore on AC Power Loss by IO


This setting specifies how your system should behave after a power fail or interrupts occurs. By choosing Disabled will leave the computer in the power off state. Choosing Enabled will restore the system to the status before power failure or interrupt occurs.

Options: Power Off (Default) / Power On / Last State

TPower I55 BIOS Manual

Hardware Health Configuration

This item shows the system temperature, fan speed, and voltage information.



H/W Health Function

If with a monitoring system, the system will show PC health status during POST stage.
Options: Enabled (Default) / Disabled


Shutdown Temperature

This item allows you to set up the CPU shutdown Temperature. This item is only effective under Windows 98 ACPI mode.

Options: Disabled (Default) / 60°C/140°F / 65°C/149°F / 70°C/158°F / 75°C/167°F
/ 80°C/176°F / 85°C/185°F / 90°C/194°F

TPower I55 BIOS Manual

Smart Fan Configuration



CPU Smart Fan

This item allows you to control the CPUSmart Fan function.
Options: Disabled (default) / Auto

Smart Fan Calibration

Choose this item and then the BIOS will auto test and detect the CPU/System fan functions and show CPU/System fan speed.

Control Mode

This item provides several operation modes of the fan.
Options: Quiet / Performance / Manual

Fan Ctrl OFF(°C)

If the CPU/System Temperature is lower than the set value, FAN will turn off.
Options: 0~127 (°C) (Interval: 1°C)

Fan Ctrl On(°C)

CPU/System fan starts to work under smart fan function when arrive this set value.
Options: 0~127 (°C) (Interval: 1°C)

TPower I55 BIOS Manual

Fan Ctrl Start Value

When CPU/System temperature arrives to the set value, the CPU/System fan will work under Smart Fan Function mode.


Options: 0~127 (Interval: 1)

Fan Ctrl Sensitive

Increasing the value will raise the speed of CPU/System fan.

Options: 1~127 (Interval: 1)

ACPI Configuration



Suspend mode

The item allows you to select the suspend type under the ACPI operating system.

Options: S1 (POS) (Default) Power on Suspend
S3 (STR) Suspend to RAM
Auto POS+STR

Repost Video on S3 Resume

The item allows you to determine whether to invoke VGA BIOS post on S3/STR resume.

Options: No (Default) / Yes

TPower I55 BIOS Manual

ACPI Version Features

The item allows you to select the version of ACPI

Options: ACPI v1.0 (Default) / ACPI v2.0 / ACPI v3.0

ACPI APIC support

This item is used to enable or disable the motherboard's APIC (Advanced Programmable Interrupt Controller). The APIC provides multiprocessor support, more IRQs and faster interrupt handling.

Options: Enabled (Default) / Disabled

AMI OEMB table

Set this value to allow the ACPI BIOS to add a pointer to an OEMB table in the Root System Description Table (RSDT) table.

Options: Enabled (Default) / Disabled

Headless mode

This is a server-specific feature. A headless server is one that operates without a keyboard, monitor or mouse. To run in headless mode, both BIOS and operating system (e.g. Windows Server 2003) must support headless operation.

Options: Disabled (Default) / Enabled

APIC ACPI SCI IRQ

Options: Disabled (Default) / Enabled

USB Device Wakeup from S3/S4

This item allows you to enable or disabled the USB resume from S3/S4 function.

Options: Disabled (Default) / Enabled

High Performance Event Timer

This item allows you to enable or disabled the HPET.

Options: Disabled (Default) / Enabled

TPower I55 BIOS Manual

Resume On PME#

When you select Enabled, a PME signal from PCI card returns the system to Full ON state.

For this function to work, you may need a LAN add-on card which supports the Wake on LAN function. Set the Wake on LAN (WOL) jumper on motherboard to enable if applicable.

Options: Disabled (Default) / Enabled

Resume On RTC Alarm

When “Enabled”, you can set the date and time at which the RTC (real-time clock) alarm awakens the system from Suspend mode.

Options: Disabled (Default) / Enabled


RTC Alarm Date (Days)

You can choose which date the system will boot up.

System Time

You can choose the system boot up time, input hour, minute and second to specify.

Onboard PCI/PCI-E Devices Configuration



TPower I55 BIOS Manual

JMicron 36x ATA Controller

This item allows you to select ATA controller operate mode.

Options: IDE Mode (Default) / RAID+IDE Mode / AHCI+IDE Mode / Disabled

Onboard IEEE 1394 Controller

This item allows you to activate IEEE 1394 Controller.

Options: Enabled (Default) / Disabled

GbE Controller

This item allows you to control GbE Controller.

Options: Enabled (Default) / Disabled

GbE LAN Boot

This item allows you to select the GbE LAN Boot.

Options: Disabled (Default) / Enabled

Onboard PCIE Giga LAN

This item allows you to control the Onboard LAN.

Options: Auto (Default) / Enabled / Disabled

Onboard LAN Boot Rom

This item allows you to select the Onboard LAN Boot ROM.

Options: Disabled (Default) / Enabled

Onboard Intel LANMAC ID


This item shows Intel LAN MAC ID.

Onboard LAN MAC ID

This item shows LAN MAC ID.

TPower I55 BIOS Manual

Intel VT-d Configuration




Intel VT-d

Intel(R) Virtualization Technology for Directed I/O (VT-d) provides hardware assists for virtualization, improving security, reliability, and performance of I/O devices in virtualized environment.

Options: Disabled (Default) / Enabled

MPS Configuration



TPower I55 BIOS Manual


MPS Revision

The BIOS supports version 1.1 and 1.4 of the Intel multiprocessor specification.
Select version supported by the operating system running on this computer.
Option: 1.4 (Default) / 1.1

MPS and ACPI MADT ordering

Modern ordering is for Windows XP or later OSes. Legacy ordering is for Windows 2000 or earlier OSes.
Option: Modern ordering (Default) / Legacy ordering

PCI Express Configuration




Active State Power-Management

This item sets the ASPM configuration for the PCI Express devices before the operating system boots. This function is for OS which does not support ASPM.
Options: Disabled (Default) / Enabled

TPower I55 BIOS Manual

Smbios Configuration




Smbios Smi Support

SMBIOS SMIWrapper support for PnP func 50h-54h.
Option: Enabled (Default) / Disabled

USB Configuration

This item shows the USB controller and using USB device information.



TPower I55 BIOS Manual

Legacy USB Support

This item determines if the BIOS should provide legacy support for USB devices like the keyboard, mouse, and USB drive. This is a useful feature when using such USB devices with operating systems that do not natively support USB (e.g. Microsoft DOS or Windows NT).

Options: Enabled (Default) / Disabled

USB 2.0 Controller Mode

This item allows you to select the operation mode of the USB 2.0 controller.

Options: HiSpeed (Default) USB 2.0-480Mbps
FullSpeed USB 1.1-12Mbps

BIOS EHCI Hand-Off

This item allows you to enable support for operating systems without an EHCI hand-off feature.


Options: Enabled (Default) / Disabled

Legacy USB1.1 HC Support

This item allows you to activate USB 1.1 HC support.

Options: Enabled (Default) / Disabled

USB Mass Storage Device Configuration



TPower I55 BIOS Manual

USB Mass Storage Reset Delay

This item allows you to set the reset delay for USB mass storage device.

Options: 20 Sec (Default) / 10 Sec / 30Sec / 40Sec

Emulation Type

This item allows you to select the emulation type of the USB mass storage device.

Options: Auto (Default) / Floppy / Forced FDD / Hard Disk / CDROM


TPower I55 BIOS Manual

3 PCIPnP Menu

This section describes configuring the PCI bus system. PCI, or Personal Computer Interconnect, is a system which allows I/O devices to operate at speeds nearing the speed of the CPU itself when communicating with its own special components.

Notice

- Beware of that setting inappropriate values in items of this menu may cause system to malfunction.



Clear NVRAM

This item allows you to clear the data in the NVRAM (CMOS) by selecting “Yes”.
Options: No (Default) / Yes

Plug & Play OS

When set to YES, BIOS will only initialize the PnP cards used for the boot sequence (VGA, IDE, SCSI). The rest of the cards will be initialized by the PnP operating system like Window™ 95. When set to NO, BIOS will initialize all the PnP cards. For non-PnP operating systems (DOS, Netware™), this option must be set to NO.

Options: No (Default) / Yes

TPower I55 BIOS Manual

PCI Latency Timer

This item controls how long a PCI device can hold the PCI bus before another takes over. The longer the latency, the longer the PCI device can retain control of the bus before handing it over to another PCI device.

Options: 64 (Default) / 32 / 96 / 128 / 160 / 192 / 224 / 248

Allocate IRQ to PCI VGA

This item allows BIOS to choose a IRQ to assign for the PCI VGA card.

Options: Yes (Default) / No

Palette Snooping

Some old graphic controllers need to “snoop” on the VGA palette and then map it to their display as a way to provide boot information and VGA compatibility. This item allows such snooping to take place.

Options: Disabled (Default) / Enabled

PCI IDE BusMaster

This item is a toggle for the built-in driver that allows the onboard IDE controller to perform DMA (Direct Memory Access) transfers.

Options: Enabled (Default) / Disabled

OffBoard PCI/ISA IDE Card

Some PCI IDE cards may require this to be set to the PCI slot number that is holding the card.

Options: Auto (Default) / PCI Slot1 ~ 6

OffBoard PCI/ISA Primary & Secondary IRQ

This item allows you to set IRQ of non-onboard PCI/ISA IDE controller adapter.

Options: Disabled (Default) / INT A / INTB / INT C / INT D / Hardwired

IRQ3/4/5/7/9/10/11/14/15

These items will allow you to assign each system interrupt a type, depending on the type of device using the interrupt. The option “Available” means the IRQ is going to assign automatically.

Options: Available (Default) / Reserved

TPower I55 BIOS Manual

DMA Channel 0/1/3/5/6/7

These items will allow you to assign each DMA channel a type, depending on the type of device using the channel. The option “Available” means the channel is going to assign automatically.

Options: Available (Default) / Reserved

Reserved Memory Size


This item allows BIOS to reserve certain memory size for specific ISA device.

Options: Disabled (Default) / 16K / 32K / 64K


TPower I55 BIOS Manual

4 Boot Menu

This menu allows you to setup the system boot options.



Boot Settings Configuration



TPower I55 BIOS Manual

Quick Boot

Enabling this option will cause an abridged version of the Power On Self-Test (POST) to execute after you power up the computer.

Options: Enabled (Default) / Disabled

Full Screen LOGO Display

This item allows you to enable/disable Full Screen LOGO Show function.

Options: Enabled (Default) / Disabled

AddOn ROM Display Mode

This item sets the display mode for option ROM.

Options: Force BIOS (Default) / Keep Current

Bootup Num-Lock

Selects the NumLock State after the system switched on.

Options: ON (Default) / OFF

PS/2 Mouse Support

This BIOS feature determines if the BIOS should reserve IRQ12 for the PS/2 mouse or allow other devices to make use of this IRQ.

Options: Auto (Default) / Disabled / Enabled

Wait for ‘F1’ If Error

This BIOS feature controls the system's response when an error is detected during the boot sequence.

Options: Enabled (Default) / Disabled

Hit ‘DEL’ Message Display

This BIOS feature allows you to control the display of the Hit “DEL” to enter Setup message during memory initialization.

Options: Enabled (Default) / Disabled

TPower I55 BIOS Manual

Interrupt 19 Capture

Interrupt 19 is the software interrupt that handles the boot disk function. When set to Enabled, this item allows the option ROMs to trap interrupt 19.

Options: Disabled (Default) / Enabled

BOOT SUCCESS BEEP

When this item is set to Enabled, BIOS will let user know boot success with beep.

Options: Enabled (Default) / Disabled

Boot Device Priority

Items in this sub-menu specify the boot device priority sequence from the available devices. The number of device items that appears on the screen depends on the number of devices installed in the system.

Hard Disk Drives

The BIOS will attempt to arrange the hard disk boot sequence automatically. You can also change the booting sequence. The number of device items that appears on the screen depends on the number of devices installed in the system.

Removable Drives

The BIOS will attempt to arrange the removable drive boot sequence automatically. You can also change the booting sequence. The number of device items that appears on the screen depends on the number of devices installed in the system.

CD/DVD Drives

The BIOS will attempt to arrange the CD/DVD drive boot sequence automatically. You can also change the booting sequence. The number of device items that appears on the screen depends on the number of devices installed in the system.


TPower I55 BIOS Manual

5 Chipset Menu

This submenu allows you to configure the specific features of the chipset installed on your system. This chipset manage bus speeds and access to system memory resources, such as DRAM. It also coordinates communications with the PCI bus.


Notice

- Beware of that setting inappropriate values in items of this menu may cause system to malfunction.



TPower I55 BIOS Manual

North Bridge Configuration



Memory Remap Feature

This item allows you to enable or disable the remapping of the overlapped PCI memory above the total physical memory. Only 64-bit OS supports this function.
Options: Enabled (Default) / Disabled

Fast MRC

Enabled: While cold booting, MRC directly restores memory data from valid NVRAM without hardware training. Disabled: The cold booting with memory detection and hardware training.

Options: Disabled (Default) / Enabled

Memory Hole

You can reserve this area of system memory for ISA adapter ROM. When this area is reserved it cannot be cached. Check the user information of peripherals that need to use this area of system memory for the memory requirements.

Options: Disabled (Default) / 15M-16M


Initiate Graphic Adapter

This item allows you to select which graphics controller to use as the primary boot device.

Options: PCIE/PCI (Default) / PCI/PCIE

TPower I55 BIOS Manual

South Bridge Configuration



HDA Controller

This item allows you to control the HD Audio support.

Options: Enabled (Default) / Disabled

SMBUS Controller

This BIOS feature controls the I/O buffers for the SMBus.

Options: Enabled (Default) / Disabled

SLP_S4# Min. Assertion Width

Options: 4 to 5 seconds (Default) / 3 to 4 seconds / 24 to 3 seconds / 1 to 2 seconds


TPower I55 BIOS Manual

6 O.N.E Menu

This submenu allows you to change voltage and clock of various devices.
(However, we suggest you use the default setting. Changing the voltage and clock improperly may damage the device.)

Notice

- Beware of that setting inappropriate values in items of this menu may cause system to malfunction.




OverClock Navigator

OverClock .Navigator is designed for beginners in overclock field.
Based on many test and experiments from Biostar Engineer Team, OverClock Navigator provides 3 default overclock configurations that are able to raise the system performance.

Options: Normal (Default) / Automate OverClock / Manual OverClock

TPower I55 BIOS Manual

Auto OverClock System



The Overclock Navigator provides 3 different engines helping you to overclock your system. These engines will boost your system performance to different level.

Options:

V6 Tech Engine

This engine will make a good over-clock performance.

V8 Tech Engine


This engine will make a better over-clock performance.

V12 Tech Engine

This engine will make a best over-clock performance.

TPower I55 BIOS Manual

Manual Overclock System (M.O.S.)



MOS is designed for experienced overclock users.
It allows users to customize personal overclock setting.

Over Clock Retry Count

This item allows you to set retry count of over clock.
Options: 1 (Default) / 2 / 3

Intel(R) SpeedStep(tm) Tech

This item allows you to enable SpeedStep technology for better power saving.
SpeedStep is a technology built into some Intel processors that allows the clock speed of the processor to be dynamically changed by software.
Options: Enabled (Default) / Disabled

Ratio CMOS Setting

This item allows you to set the CPU ratio frequency. This item is adjustable only when SpeedStep Tech is set to Disabled.
Options: x20.0 (Default) / x9.0 ~ x21.0

CPU Frequency Setting

This item allows you to select the CPU Frequency.
Options: Min= 100MHz; Max= 800MHz


TPower I55 BIOS Manual

DRAM Frequency

This item allows you to control the Memory Clock.

Options: Auto (Default) / 800MHz / 1067MHz / 1333MHz

DRAM Timing Configuration



DRAM Frequency

This item allows you to control the Memory Clock.

Options: Auto (Default) / 800MHz / 1067MHz / 1333MHz

DRAM Timing Control By

This item allows you to choose to manually or automatically regulate the DRAM Timing.

Options: Auto (Default) / Manual

DRAM tCL

Options: 9 (Default) / 3 ~ 15

DRAM tRCD

Options: 9 (Default) / 3 ~ 15

TPower I55 BIOS Manual

DRAM tRP

Options: 9 (Default) / 3 ~ 15

DRAM tRAS

Options: 24 (Default) / 9 ~ 63

DRAM tRRD

Options: 4 (Default) / 5 ~ 15

DRAM tWR

Options: 10 (Default) / 3 ~ 31

DRAM tWTR

Options: 5 (Default) / 4 ~ 31

DRAM tRTP

Options: 5 (Default) / 4 ~ 15

DRAM tRFC

Options: 74 (Default) / 15 ~ 255

DRAM tFAW

Options: 20 (Default) / 15 ~ 63

DRAM Command Rate

This item allows you to select command rate of DDR3.

Options: 1T (Default) / 2T

DRAM Round Trip Latency by

This item allows you to choose to manually or automatically regulate the DRAM Round Trip Latency

Options: Auto (Default) / Manual

TPower I55 BIOS Manual

DRAM ChA/ChB Round Trip Latency

Options: 1 (Default) / 2 ~ 255

DRAM R-R delay same Rank

Options: Auto (Default) / 4 / 6

DRAM R-R delay diff Rank

Options: Auto (Default) / 2 ~ 9

DRAM R-W delay same Rank

Options: Auto (Default) / 2 ~ 17

DRAM R-W delay diff Rank

Options: Auto (Default) / 2 ~ 17

DRAM R-W delay same Rank

Options: Auto (Default) / 2 ~ 17

DRAM W-R delay same Rank

Options: Auto (Default) / 10~25

DRAM W-R delay diff Ranks


Options: Auto (Default) / 1 ~ 8

DRAM W-R delay diff DIMMs

Options: Auto (Default) / 1 ~ 8

TPower I55 BIOS Manual

Clock Gen Configuration



PCIE Clock By

This item allows you to determine how to set PCIE Clock, by auto or manual.
Options: Auto (Default) / Manual

PCIE Frequency Setting

This item allows you to select the PCIE clock control.
Options: 100 (Default) / Min=100; Max=150

CPU Clock delay


This item allows you to select CPU Clock delay.
Options: No delay (Default) / 50ps / 100ps / 150ps / 200ps / 250ps / 300ps / 350ps
/ 400ps / 450ps / 500ps

(G)MCH Clock delay

This item allows you to select MCH Clock delay.
Options: No delay (Default) / 50ps / 100ps / 150ps / 200ps / 250ps / 300ps / 350ps
/ 400ps / 450ps / 500ps

TPower I55 BIOS Manual

Voltage Control



CPU Voltage

This item allows you to select Over CPU Voltage Control.

Options: Auto (Default) / +0.00625V ~+0.78750V (Interval: 0.00625V)

CPU VTT Voltage

This item allows you to select CPU VTT Over Voltage Control.

Options: Auto (Default) / 1.100V ~ +2030V (Interval: 0.015V)

CPU VTT PWR Phase Freqsel

This item allows you to select CPU VTT PWR Phase Freqsel Control.

Options: Auto (Default) / +20% / +40% / +60% / +80%

CPU PLL Voltage

This item allows you to select CPU PLL Voltage Control.

Options: Auto (Default) / 1.800V ~ 2.730V (Interval: 0.015V)

CPU Phase Freq

This item allows you to select CPU Phase Freq Control.

Options: Default (Default) / -20% / +20% / +40%

TPower I55 BIOS Manual

DRAM Voltage

This item allows you to select DRAM Voltage Control.
Options: Auto (Default) / 1.600V ~ 2.530V (Interval: 0.015V)

DRAM Channel-A/B CMD/ADD VREF

This item allows you to select DRAM Channel-A/B CMD/ADD VREF Control.
Options: Default (Default) / 38% ~ 62%

DRAM Channel-A/B DQS VREF

This item allows you to select DRAM Channel-A/B DQS VREF Control.
Options: Default (Default) / 38% ~ 62%

DRAM PWR Phase Freqsel

This item allows you to select DRAM PWR Phase Freqsel Control.
Options: Default (Default) / +30% / +60% / +90%

PCH Voltage

This item allows you to select PCH Voltage Control.
Options: Auto (Default) / 1.100V ~ 2.030V (Interval: 0.015V)

PCH PLL Voltage

This item allows you to select PCH PLL Voltage Control.
Options: Auto (Default) / 1.05V ~ 2.025V (Interval: 0.015V)

PCH ME Voltage

This item allows you to select PCH ME Voltage Control.
Options: Auto (Default) / 1.05V ~ 2.025V (Interval: 0.015V)

CLOCK Gen Voltage


This item allows you to select CLOCK Gen Voltage Control.
Options: Auto (Default) (Interval: 0.015V)

CPU Load line

This item allows you to load line control.
Options: Enabled (Default) / Disabled

TPower I55 BIOS Manual

Intel PPM Configuration



Intel(R) SpeedStep(tm) tech

This item allows you to enable SpeedStep technology for better power saving. SpeedStep is a technology built into some Intel processors that allows the clock speed of the processor to be dynamically changed by software.

Options: Enabled (Default) / Disabled

Intel(R) Turbo Mode tech

Turbo mode allows processor cores to run faster than marked frequency in specific condition.

Options: Enabled (Default) / Disabled

Intel(R) C-STATE Tech

This item allows you to control the C-State power management functions of the processor. (CState: CPU idle is set to C2/C3/C4)

Options: Enabled (Default) / Disabled

C State package limit setting

The selected option will program into C State package limit register.
Options: Auto (Default) / C1 / C3 / C6 / C7

TPower I55 BIOS Manual

C3 State

This item allows you to select Nehalem C state action.
Options: ACPI C2 (Default) / ACPI C3 / Disabled

C6 State

This item allows you to select Nehalem C state action.
Options: Enabled (Default) / Disabled


C1 Auto Demotion

When enabled, CPU will conditionally demote C3/C6/C7 requests to C1 based on uncore auto-demote information.
Options: Enabled (Default) / Disabled

C3 Auto Demotion

When enabled, CPU will conditionally demote C6/C7 requests to C3 based on uncore auto-demote information.
Options: Enabled (Default) / Disabled

BIOS STAR Memory Insight




DDR3-A1/B1/A2/B2 SPD Informations

These items display SPD information of DDR3 memory.

TPower I55 BIOS Manual

G.P.U Phase Control



G.P.U Phase Mode

This item allows you to control G.P.U Phase Mode (power saving technology).
Options: Auto (Default) / Off

CPU VTT Phase Mode

This item allows you to select CPU VTT Phase Mode.
Options: Full on (Default) / Energy saving


TPower I55 BIOS Manual

Integrated Memory Test

Integrated Memory Test allows users to test memory module compatibilities without additional device or software.


Step 1:

This item is HotKey F11 on default; change it to “Enable” to precede memory test.



Step 2:


When the process is done, change the setting back from “Enabled” to “HotKey F11” or “Disabled” to complete the test.



TPower I55 BIOS Manual

7 Exit Menu

This menu allows you to load the optimal default settings, and save or discard the changes to the BIOS items.



Save Changes and Exit

Save all configuration changes to CMOS RAM and exit setup.

Discard Changes and Exit

Abandon all changes made during the current session and exit setup.

Discard Changes

Abandon all changes made during the current session and restore the previously saved values.


Load Optimal Defaults

This selection allows you to reload the BIOS when problem occurs during system booting sequence. These configurations are factory settings optimized for this system.

TPower I55 BIOS Manual

Security

This sub-menu allows you to provide/revise supervisor and user password.



Change Supervisor Password

Setting the supervisor password will prohibit everyone except the supervisor from making changes using the CMOS Setup Utility. You will be prompted with to enter a password.

User Acess Level

This item allows supervisor to set the user level.

Options: Full Access (Default) / No Access / View Only / Limited

Change User Password

If the Supervisor Password is not set, then the User Password will function in the same way as the Supervisor Password. If the Supervisor Password is set and the User Password is set, the "User" will only be able to view configurations but will not be able to change them.

Clear User Passw ord

This item is for clearing user password.

TPower I55 BIOS Manual

Password Check

This item is for setting the timing that checking password.
Options: Setup (Default) / Always

Boot Sector Virus Protection

This option allows you to choose the VIRUS Warning feature that is used to protect the IDE Hard Disk boot sector. If this function is enabled and an attempt is made to write to the boot sector, BIOS will display a warning message on the screen and sound an alarm beep.

Options: Disabled (Default) / Enabled

CMOS Backup Function

It allows users to save different CMOS settings into BIOS-ROM and reload any saved CMOS setting for customizing system configurations.

Moreover, users are able to save an ideal overclock setting during overclock operation.

There are 10 sets of record addresses in total, and users are able to name the CMOS data according to personal preference.

