

EIQ37-ANT

specification



| | |
|-----------------------------|---|
| Form Factor | uATX 198*170mm |
| Chipset | Q370 |
| CPU | LGA1151 support Intel 8/9 th Core CPU, up to 95W |
| Memory | 2*SO-DIMM , support Dual-channel DDR4-2666, up to 32GB |
| Video | DPx2(1 from CPU/ 1 from MXM VGA card), LVDS/eDP by BOM opt |
| LAN | 1* 1G LAN by Intel i219LM + 1*1G LAN by Intel i211AT |
| Codec | Realtek ALC897 w/ ALC105, support 3W Speaker_out |
| Expansion slot | 1*MXM slot for MXM Type B Plus 1*M.2 key B(3042/3052), support USB3.2 Gen1 + PCIe1 w/ nano SIM card, 1*M.2 Key M, support PCIe4 / SATA 1*Full size Mini PCI-E, support PCIe1 +USB2.0 |
| onboard IO | 2*2x5 pin header for RS232 2*2x4 pin header for USB2.0 (support 4 ports USB2.0) 2*SATA port 1*1x4 pin for SATA power 1*eDP header(BOM opt) 1*LVDS header 1*LVDS inverter header 1*2x3 pin header for LCD voltage select 1*2x5 pin header for Front Panel 1*2x5pin header for 8 bit DIO 1*1x4 Speaker_out header 2*1x3 CAN bus header 1*1x4 pin CPU fan header 1*1x4 pin System fan header 1*1x4 pin MXM fan header TPM 2.0 by BOM opt (Infineon SLB9665XT) |
| Rear IO | 2*Display port 6*USB3.2 Gen 1 port 2*1G RJ45 1*DC Jack (12V/19V) 1*2 port audio jack for Line_out / MIC-in |
| Ordering information | EIQ37ANT-R02-BS300(LVDS) |



