

FCC Information and Copyright

This equipment has been tested and found to comply with the limits of a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. There is no guarantee that interference will not occur in a particular installation.

The vendor makes no representations or warranties with respect to the contents here and specially disclaims any implied warranties of merchantability or fitness for any purpose. Further the vendor reserves the right to revise this publication and to make changes to the contents here without obligation to notify any party beforehand.

Duplication of this publication, in part or in whole, is not allowed without first obtaining the vendor's approval in writing.

The content of this user's manual is subject to be changed without notice and we will not be responsible for any mistakes found in this user's manual. All the brand and product names are trademarks of their respective companies.

Table of Contents

Chapter 1: Introduction	1
1.1 Before You Start	1
1.2 Package Checklist	1
1.3 Motherboard Features	2
1.4 Rear Panel Connectors	3
1.5 Motherboard Layout	4
Chapter 2: Hardware Installation	5
2.1 Installing Central Processing Unit (CPU)	5
2.2 FAN Headers	7
2.3 Installing System Memory	8
2.4 Connectors and Slots	10
Chapter 3: Headers & Jumpers Setup	12
3.1 How to Setup Jumpers	12
3.2 Detail Settings	12
Chapter 4: T-Series BIOS & Software	19
4.1 T-Series BIOS	19
4.2 T-Series Software	27
Chapter 5: Useful Help	36
5.1 Driver Installation Note	36
5.2 Extra Information	37
5.3 AMI BIOS Beep Code	38
5.4 Troubleshooting	39
Appendix: SPEC In Other Languages	40
German	40
French	42
Italian	44
Spanish	46
Portuguese	48
Polish	50
Russian	52
Arabic	54
Japanese	56

CHAPTER 1: INTRODUCTION

1.1 BEFORE YOU START

Thank you for choosing our product. Before you start installing the motherboard, please make sure you follow the instructions below:

- Prepare a dry and stable working environment with sufficient lighting.
- Always disconnect the computer from power outlet before operation.
- Before you take the motherboard out from anti-static bag, ground yourself properly by touching any safely grounded appliance, or use grounded wrist strap to remove the static charge.
- Avoid touching the components on motherboard or the rear side of the board unless necessary. Hold the board on the edge, do not try to bend or flex the board.
- Do not leave any unfastened small parts inside the case after installation. Loose parts will cause short circuits which may damage the equipment.
- Keep the computer from dangerous area, such as heat source, humid air and water.

1.2 PACKAGE CHECKLIST

- ✚ HDD Cable X 1
- ✚ Serial ATA Cable X 2
- ✚ Rear I/O Panel for ATX Case X 1
- ✚ User's Manual X 1
- ✚ Fully Setup Driver CD X 1
- ✚ FDD Cable X 1 (optional)
- ✚ USB 2.0 Cable X1 (optional)
- ✚ Serial ATA Power Cable X 1 (optional)

Note: The package contents may be different due to area or your motherboard version.


1.3 MOTHERBOARD FEATURES

	<i>TP43E XE/TP43E HP</i>	<i>TP45E HP</i>
CPU	LGA 775 Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx processor Supports Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technology	LGA 775 Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx processor Supports Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technology
FSB	Support 800 / 1066 / 1333 / 1600 MHz	Support 800 / 1066 / 1333 / 1600 MHz
Chipset	Intel P43 Intel ICH10	Intel P45 Intel ICH10
Super I/O	ITE 8718F Provides the most commonly used legacy Super I/O functionality. Low Pin Count Interface Environment Control initiatives, Hardware Monitor Controller Fan Speed Controller ITE's "Smart Guardian" function	ITE 8718F Provides the most commonly used legacy Super I/O functionality. Low Pin Count Interface Environment Control initiatives, Hardware Monitor Controller Fan Speed Controller ITE's "Smart Guardian" function
Main Memory	DIMM Slots x 4 Each DIMM supports 256MB / 512MB / 1GB / 2GB / 4GB DDR2 Max Memory Capacity 16GB Dual Channel Mode DDR2 memory module Supports DDR2 1200 (OC) / 1066 / 800 / 667 Registered DIMM and ECC DIMM is not supported	DIMM Slots x 4 Each DIMM supports 256MB / 512MB / 1GB / 2GB / 4GB DDR2 Max Memory Capacity 16GB Dual Channel Mode DDR2 memory module Supports DDR2 1200 (OC) / 1066 / 800 / 667 Registered DIMM and ECC DIMM is not supported
IDE	JMicro JMB368 Ultra DMA 33 / 66 / 100 / 133 Bus Master Mode supports PIO Mode 0~4	JMicro JMB368 Ultra DMA 33 / 66 / 100 / 133 Bus Master Mode supports PIO Mode 0~4
SATA 2	Integrated Serial ATA Controller Data transfer rates up to 3.0 Gb/s. SATA Version 2.0 specification compliant	Integrated Serial ATA Controller Data transfer rates up to 3.0 Gb/s. SATA Version 2.0 specification compliant
LAN	Realtek RTL 8111DL 10 / 100 Mb/s / 1Gb/s auto negotiation Half / Full duplex capability	Realtek RTL 8111DL 10 / 100 Mb/s / 1Gb/s auto negotiation Half / Full duplex capability
Sound Codec	ALC888 7.1 channels audio out High Definition Audio	ALC888 7.1 channels audio out High Definition Audio


TP43E XE/TP43E HP/TP45E HP

	TP43E XE/TP43E HP		TP45E HP	
Slots	PCI slot	x3	PCI slot	x3
	PCI Express Gen2 x 16 slot	x1	PCI Express Gen2 x 16 slot	x1
	PCI Express x 1 slot	x2	PCI Express x 1 slot	x2
On Board Connector	Floppy connector	x1	Floppy connector	x1
	IDE Connector	x1	IDE Connector	x1
	SATA Connector	x6	SATA Connector	x6
	Front Panel Connector	x1	Front Panel Connector	x1
	Front Audio Connector	x1	Front Audio Connector	x1
	CD-in Connector	x1	CD-in Connector	x1
	CPU Fan header	x1	CPU Fan header	x1
	System Fan header	x2	System Fan header	x2
	Clear CMOS header	x1	Clear CMOS header	x1
	USB connector	x3	USB connector	x3
Back Panel I/O	Power Connector (24pin)	x1	Power Connector (24pin)	x1
	Power Connector (4pin)	x2	Power Connector (4pin)	x2
	PS/2 Keyboard	x1	PS/2 Keyboard	x1
	PS/2 Mouse	x1	PS/2 Mouse	x1
	LAN port	x1	LAN port	x1
Back Panel I/O	USB Port	x6	USB Port	x6
	Audio Jack	x6	Audio Jack	x6
	Optical +coaxial S/PDIF Out	x1	Optical +coaxial S/PDIF Out	x1
	Board Size	220 (W) x 305 (L) mm		220 (W) x 305 (L) mm
OS Support	Windows XP / VISTA 32 / VISTA 64		Windows XP / VISTA 32 / VISTA 64	
	Biostar reserves the right to add or remove support for any OS with or without notice		Biostar reserves the right to add or remove support for any OS with or without notice	

1.4 REAR PANEL CONNECTORS




1.5 MOTHERBOARD LAYOUT



Note: ■ represents the 1st pin.


CHAPTER 2: HARDWARE INSTALLATION

2.1 INSTALLING CENTRAL PROCESSING UNIT (CPU)




Special Notice:

Remove Pin Cap before installation, and make good preservation for future use. When the CPU is removed, cover the Pin Cap on the empty socket to ensure pin legs won't be damaged.




Step 1: Pull the socket locking lever out from the socket and then raise the lever up to a 90-degree angle.




Motherboard Manual

Step 2: Look for the triangular cut edge on socket, and the golden dot on CPU should point forwards this triangular cut edge. The CPU will fit only in the correct orientation.

Step 2-1:



Step 2-2:



Step 3: Hold the CPU down firmly, and then lower the lever to locked position to complete the installation.




Step 4: Put the CPU Fan and heatsink assembly on the CPU and buckle it on the retention frame. Connect the CPU FAN power cable into the JCFAN1. This completes the installation.

2.2 FAN HEADERS


These fan headers support cooling-fans built in the computer. The fan cable and connector may be different according to the fan manufacturer. Connect the fan cable to the connector while matching the black wire to pin#1.

CPU_FAN1: CPU Fan Header



Pin	Assignment
1	Ground
2	+12V
3	FAN RPM rate sense
4	Smart Fan Control

NB_FAN1/SYS_FAN1: System Fan Headers




Pin	Assignment
1	Ground
2	+12V
3	FAN RPM rate sense

Note:


The NB_FAN1/SYS_FAN1 support 3-pin head connectors; the CPU_FAN1 supports 4-pin head connector. When connecting with wires onto connectors, please note that the red wire is the positive and should be connected to pin#2, and the black wire is Ground and should be connected to GND.

2.3 INSTALLING SYSTEM MEMORY


A. Memory Modules



1. Unlock a DIMM slot by pressing the retaining clips outward. Align a DIMM on the slot such that the notch on the DIMM matches the break on the Slot.



2. Insert the DIMM vertically and firmly into the slot until the retaining chip snap back in place and the DIMM is properly seated.



B. Memory Capacity

DIMM Socket Location	DDR2 Module	Total Memory Size
DDR2_A1	256MB/512MB/1GB/2GB/4GB	Max is 16GB.
DDR2_A2	256MB/512MB/1GB/2GB/4GB	
DDR2_B1	256MB/512MB/1GB/2GB/4GB	
DDR2_B2	256MB/512MB/1GB/2GB/4GB	

C. Dual Channel Memory installation

Please refer to the following requirements to activate Dual Channel function:

Install memory module of the same density in pairs, shown in the table.

Dual Channel Status	DDR2_A1	DDR2_A2	DDR2_B1	DDR2_B2
Enabled	O	X	O	X
Enabled	X	O	X	O
Enabled	O	O	O	O


(O means memory installed, X means memory not installed.)

The DRAM bus width of the memory module must be the same (x8 or x16)

2.4 CONNECTORS AND SLOTS

FDD1: Floppy Disk Connector


The motherboard provides a standard floppy disk connector that supports 360K, 720K, 1.2M, 1.44M and 2.88M floppy disk types. This connector supports the provided floppy drive ribbon cables.



IDE1: Hard Disk Connector

The motherboard has a 32-bit Enhanced PCI IDE Controller that provides PIO Mode 0~4, Bus Master, and Ultra DMA 33/66/100/133 functionality.

The IDE connector can connect a master and a slave drive, so you can connect up to two hard disk drives.




PEX16_1: PCI-Express Gen2 x16 Slot

- PCI-Express 2.0 compliant.
- Maximum theoretical realized bandwidth of 8GB/s simultaneously per direction, for an aggregate of 16GB/s totally.
- PCI-Express Gen2 supports a raw bit-rate of 5.0Gb/s on the data pins.
- 2X bandwidth over the PCI-Express 1.1 architecture.


PEX1_1/PEX1_2: PCI-Express x1 Slots

- PCI-Express 1.1 compliant.
- Data transfer bandwidth up to 250MB/s per direction; 500MB/s in total.
- PCI-Express supports a raw bit-rate of 2.5Gb/s on the data pins.
- 2X bandwidth over the PCI architecture.



PCI1~PCI3: Peripheral Component Interconnect Slots


This motherboard is equipped with 3 standard PCI slots. PCI stands for Peripheral Component Interconnect, and it is a bus standard for expansion cards. This PCI slot is designated as 32 bits.



CHAPTER 3: HEADERS & JUMPERS SETUP

3.1 HOW TO SETUP JUMPERS


The illustration shows how to set up jumpers. When the jumper cap is placed on pins, the jumper is “close”, if not, that means the jumper is “open”.



3.2 DETAIL SETTINGS

PANEL1: Front Panel Header


This 16-pin connector includes Power-on, Reset, HDD LED, Power LED, and speaker connection. It allows user to connect the PC case’s front panel switch functions.



Pin	Assignment	Function	Pin	Assignment	Function
1	+5V	Speaker Connector	9	N/A	N/A
2	N/A		10	N/A	N/A
3	N/A		11	N/A	N/A
4	Speaker	Hard drive LED	12	Power LED (+)	Power LED
5	HDD LED (+)		13	Power LED (+)	
6	HDD LED (-)	Reset button	14	Power LED (-)	
7	Ground		15	Power button	
8	Reset control		16	Ground	

ATXPWR1: ATX Power Source Connector


This connector allows user to connect 24-pin power connector on the ATX power supply.



Pin	Assignment	Pin	Assignment
13	+3.3V	1	+3.3V
14	-12V	2	+3.3V
15	Ground	3	Ground
16	PS_ON	4	+5V
17	Ground	5	Ground
18	Ground	6	+5V
19	Ground	7	Ground
20	NC	8	PW_OK
21	+5V	9	Standby Voltage+5V
22	+5V	10	+12V
23	+5V	11	+12V
24	Ground	12	+3.3V

ATXPWR2: ATX Power Source Connector

This connector provides +12V to CPU power circuit.





Pin	Assignment
1	+12V
2	+12V
3	Ground
4	Ground

Note:

Before you power on the system, please make sure that both ATXPWR1 and ATXPWR2 connectors have been well plugged-in.

AUXPWR1: Auxiliary Power for Graphics



This connector is an auxiliary power connection for graphics cards. Exclusive power for the graphics card provides better graphics performance.



Pin	Assignment
1	+12V
2	Ground
3	Ground
4	VCC

SATA1~SATA6: Serial ATA Connectors


The motherboard has a PCI to SATA Controller with 6 channels SATA interface, it satisfies the SATA 2.0 spec and with transfer rate of 3.0Gb/s.



Pin	Assignment
1	Ground
2	TX+
3	TX-
4	Ground
5	RX-
6	RX+
7	Ground

F_USB1/F_USB2/F_USB3: Headers for USB 2.0 Ports at Front Panel


These headers allow user to connect additional USB cable on the PC front panel, and also can be connected with internal USB devices, like USB card reader.



Pin	Assignment
1	+5V (fused)
2	+5V (fused)
3	USB-
4	USB-
5	USB+
6	USB+
7	Ground
8	Ground
9	Key
10	NC

F_AUDIOF1: Front Panel Audio Header



This header allows user to connect the front audio output cable with the PC front panel. This header allows only HD audio front panel connector; AC'97 connector is not acceptable.



Pin	Assignment
1	Mic Left in
2	Ground
3	Mic Right in
4	GPIO
5	Right line in
6	Jack Sense
7	Front Sense
8	Key
9	Left line in
10	Jack Sense

CD_IN1: CD-ROM Audio-in Connector


This connector allows user to connect the audio source from the variety devices, like CD-ROM, DVD-ROM, PCI sound card, PCI TV turner card etc..



Pin	Assignment
1	Left Channel Input
2	Ground
3	Ground
4	Right Channel Input

JCMOS1: Clear CMOS Header

Placing the jumper on pin2-3 allows user to restore the BIOS safe setting and the CMOS data. Please carefully follow the procedures to avoid damaging the motherboard.



Pin 1-2 Close:
Normal Operation (default).




Pin 2-3 Close:
Clear CMOS data.

※ Clear CMOS Procedures:

1. Remove AC power line.
2. Set the jumper to "Pin 2-3 close".
3. Wait for five seconds.
4. Set the jumper to "Pin 1-2 close".
5. Power on the AC.
6. Reset your desired password or clear the CMOS data.

On-Board LED Indicators

There are 6 LED indicators on the motherboard showing system status.



LED1 & LED2: Debug Indicators

PH1 ~ PH4: Power Status Indicators


Please refer to the tables below for specific messages:

LED1	LED2	Message
ON	ON	Normal
ON	OFF	Memory Error
OFF	ON	VGA Error
OFF	OFF	Abnormal: CPU / Chipset error.

PH1 ~ PH4	Phase Indicator
ON	Phase Active
OFF	Phase Disable

On-Board Buttons

There are 2 on-board buttons.



SW_RST: Reset button.

SW_PWR: Power Switch button.

JUSBV1/JUSBV2: Power Source Headers for USB Ports

Pin 1-2 Close:


JUSBV1: +5V for USB/PS2 ports at USB1/USB2/RJ45USB1.

JUSBV2: +5V for USB ports at F_USB1/F_USB2/F_USB3.

Pin 2-3 Close:

JUSBV1: +5V STB for USB ports at USB1/USB2/RJ45USB1.

JUSBV2: +5V STB for USB/PS2 ports at F_USB1/F_USB2/F_USB3.



CHAPTER 4: T-SERIES BIOS & SOFTWARE

4.1 T-SERIES BIOS

T-Series BIOS Features


- Overclocking Navigator Engine (O.N.E.)
- Memory Integration Test (M.I.T., under Overclock Navigator Engine)
- BIO-Flasher: Update BIOS file from USB Flash Drive or FDD
- Self Recovery System (S.R.S)
- Smart Fan Function
- CMOS Reloading Program

!! WARNING !!

For better system performance, the BIOS firmware is being continuously updated. The BIOS information described below in this manual is for your reference only and the actual BIOS information and settings on board may be different from this manual. For further information of setting up the BIOS, please refer to the BIOS Manual in the Setup CD.



A. Overclocking Navigator Engine (O.N.E.)

ONE provides two powerful overclocking engines: MOS and AOS for both Elite and Casual overclockers.



Manual Overclock System (M.O.S.)

MOS is designed for experienced overclock users. It allows users to customize personal overclock settings.



Intel(R) SpeedStep(tm) Tech

This item allows you to enable SpeedStep technology for better power saving. SpeedStep is a technology built into some Intel processors that allows the clock speed of the processor to be dynamically changed by software.

Ratio CMOS Setting

This item allows you to set the CPU ratio frequency.

CPU Frequency Setting

CPU Frequency is directly in proportion to system performance. To maintain the system stability, CPU voltage needs to be increased also when raising CPU frequency.

Over Clock Retry Count

This item allows you to set the overclock fail retry times.

FSB(Bsel) To NorthBridge Latch

This item allows you to select the FSB Frequency.

DRAM Frequency

To get better system performance, sometimes downgrading the memory frequency is necessary when CPU frequency is adjusted over the upper limit.

DDR2 Enhanced Mode

This item allows you to control the DDR2 ram enhanced mode.

DRAM Timing Configuration

Enter this item for more advanced DRAM timing settings.

Clock Gen Configuration

Enter this item for more advanced Clock Gen settings.

ALL Voltage Configuration


Enter this item for more advanced voltage settings.

NOTE

Overclock is an optional process, but not a “must-do” process; it is not recommended for inexperienced users. Therefore, we will not be responsible for any hardware damage which may be caused by overclocking. We also would not guarantee any overclocking performance.

Automatic Overclock System (A.O.S.)


For beginners in overclock field, BET had developed an easy, fast, and powerful feature to increase the system performance, named A.O.S. Based on many tests and experiments, A.O.S. provides 3 ideal overclock configurations that are able to raise the system performance in a single step.



Motherboard Manual


V6 Tech Engine

This engine will make a good over-clock performance.




V8 Tech Engine

This engine will make a better over-clock performance.



V12 Tech Engine

This engine will make a best over-clock performance.



Notices:

Not all types of Intel CPU perform above overclock setting ideally; the difference will be based on the selected CPU model.



B. Memory Integration Test (M.I.T.)

This function is under “Overclocking Navigator Engine” item.

MIT allows users to test memory compatibilities, and no extra devices or software are needed.

Step 1

The default setting under this item is “Disabled”; the condition parameter should be changed to “Enable” to proceed this test.



Step 2

Save and Exit from CMOS setup and reboot the system to activate this test.

Run this test for 5 minutes (minimum) to ensure the memory stability.

Step 3

When the process is done, change the setting back from “Enable” to “Disable” to complete the test.

C. BIO-Flasher

BIO-Flasher is a BIOS flashing utility providing you an easy and simple way to update your BIOS via USB pen drive or floppy disk.

The BIO-Flasher is built in the BIOS chip. To enter the utility, **press <F12>** during the **Power-On Self Tests (POST)** procedure while booting up.

Updating BIOS with BIO-Flasher

1. Go to the website to download the latest BIOS file for the motherboard.
2. Then, save the BIOS file into a USB pen drive or a floppy disk.
3. Insert the USB pen drive or the floppy disk that contains the BIOS file to the USB port or the floppy disk drive.
4. Power on or reset the computer and then press **<F12>** during the **POST** process. A select dialog as the picture on the right appears. Select the device contains the BIOS file and press **<Enter>** to enter the utility.



5. The utility will show the BIOS files and their respective information. Select the proper BIOS file and press **<Enter>** then **<Y>** to perform the BIOS update process.

6. After the update process, the utility will ask you to reboot the system. Press **<Y>** to proceed. BIOS update completes.



- This utility only allows storage device with FAT32/16 format and single partition.
- Shutting down or resetting the system while updating the BIOS will lead to system boot failure.

D. Self Recovery System (S.R.S.)

This function can't be seen under BIOS setup; and is always on whenever the system starts up.

However, it can prevent system hang-up due to inappropriate overclock actions.

When the system hangs up, S.R.S. will automatically log in the default BIOS setting, and all overclock settings will be re-configured.



E. Smart Fan Function

Smart Fan Function is under "Smart Fan Configuration" in "Advanced Menu".

This is a brilliant feature to control CPU/System Temperature vs. Fan speed.

When enabling Smart Fan function, Fan speed is controlled automatically by CPU/System temperature.

This function will protect CPU/System from overheat problem and maintain the system temperature at a safe level.



Smart Fan Calibration

Choose this item and then the BIOS will automatically test and detect the CPU/System fan functions and show CPU/System fan speed.

Control Mode

This item provides several operation modes of the fan.

Fan Ctrl OFF(°C)

If the CPU/System temperature is lower than the set value, the CPU/System fan will turn off. The range is from 0~127, with an interval of 1.

Fan Ctrl On(°C)

The CPU/System fan starts to work when CPU/System temperature arrives to this set value. The range is from 0~127, with an interval of 1.

Fan Ctrl Start Value


When CPU/System temperature arrives to the set value, the CPU/System fan will work under Smart Fan Function mode. The range is from 0~127, with an interval of 1.

Fan Ctrl Sensitive

Increasing the value of slope PWM will raise the speed of CPU/System fan. The range is from 1~127, with an interval of 1.

F. CMOS Reloading Program

It allows users to save different CMOS settings into BIOS-ROM. Users are able to reload any saved CMOS setting for customizing system configurations. Moreover, users are able to save an ideal overclock setting during overclock operation. There are 10 sets of record addresses in total, and users are able to name the CMOS data according to personal preference.



4.2 T-SERIES SOFTWARE

Installing T-Series Software

1. Insert the Setup CD to the optical drive. The drivers installation program would appear if the Auto-run function has been enabled.
2. Select **Software Installation**, and then click on the respective software title.
3. Follow the on-screen instructions to complete the installation.


Launching T-Series Software

After the installation process, you will see the software icon “T-Utility OverClock III” / “HW Monitor” / “eHOT Line” / “Tseries BIOS Update” appears on the desktop. Double-click the icon to launch T-Series utility.


OverClock 3

OverClock 3 is equipped with friendly interface and solid over-clock features, and it will help you easily do over-clocking under windows environment.

Double-click the desktop icon, OverClock 3 will be launched; the first window you will see is **Main Panel**. In this panel you will see current CPU Speed and CPU/Memory/PCI-E/PCI Clock.




Over Clock Panel



AUTO

User can click this button and the utility will set the best and stable performance and frequency automatically. A warning dialog as below will show up to notify you that the system may become unstable, click on “OK” to continue.



Then the utility will execute a series of testing until system fail. Then system will do fail-safe reboot by using Watchdog function. After reboot, launch the utility again and the utility will load the previously verified best and stable frequency.

V3 / V6 / V9

Provide user the ability to do real-time over-clock adjustment. For beginners in over-clock field, this is a powerful feature to increase system performance.

- **V3 Engine**
This engine will make a good over-clock performance.
- **V6 Engine**
This engine will make a better over-clock performance.
- **V9 Engine**
This engine will make a best over-clock performance.

TEST

You can also manually adjust CPU clock by pressing +/- button or moving the level bar. After manually adjust the CPU clock, you should click TEST button and the utility will proceed a testing for current frequency. If the testing is ok, then the current frequency will be saved into system registry. If the testing fails, system will do a fail-safe rebooting. After reboot, the utility will restore to the hardware default setting.


Warning

Manually over-clock is potentially dangerous, especially when the over-clocking percentage is over 110 %. We strongly recommend you test every speed you over-clock by click the TEST button. Or, you can just click AUTO over-clock button and let the Utility automatically get the best result for you.

RESET

Click this button and the utility will restore all values to the hardware default setting.

Over Voltage Panel



CPU Voltage

This function allows user to adjust CPU voltage. Click on “+” to increase or “-” to decrease the CPU voltage.

Memory Voltage

This function allows user to adjust Memory voltage. Click on “+” to increase or “-” to decrease the Memory voltage.

Chip Voltage

This function allows user to adjust Chipset voltage. Click on “+” to increase or “-” to decrease the Chipset voltage.

FSB Voltage


This function allows user to adjust FSB voltage. Click on “+” to increase or “-” to decrease the FSB voltage.

About Panel

In this panel, you can get model name and other system information that may related to over-clocking. You can also get the version number of this software.


Note

Because the Over Clock and Over Voltage features are controlled by several separate chipset, the utility divides these features to separate panels. If one chipset is not on board, the correlative button in Main panel will be disabled, but it will not interfere with other panels' functions. This property can make the utility more robust.



Hardware Monitor

HW Monitor is a monitor utility that helps you to maintain the health of the PC. It provides real-time information of CPU/GPU/System temperature, fan speed, and voltage.



eHot-Line (Optional)


eHot-Line is a convenient utility that helps you to contact with our Tech-Support system. This utility will collect the system information which is useful for analyzing the problem you may have encountered, and then send these information to our tech-support department to help you fix the problem.

 Before you use this utility, please set Outlook Express as your default e-mail client application program.

* represents important information that you must provide. Without this information, you may not be able to send out the mail.

This block will show the information which would be collected in the mail.

* Describe condition of your system.




After filling up this information, click **“Send”** to send the mail out. A warning dialog would appear asking for your confirmation; click **“Send”** to confirm or **“Do Not Send”** to cancel.



If you want to save this information to a .txt file, click **“Save As...”** and then you will see a saving dialog appears asking you to enter file name.

Enter the file name and then click “Save”. Your system information will be saved to a .txt file.



Open the saved .txt file, you will see your system information including motherboard/BIOS/CPU/video/ device/OS information. This information is also included in the sent mail.




We will not share customer’s data with any other third parties, so please feel free to provide your system information while using eHot-Line service.



If you are not using Outlook Express as your default e-mail client application, you may need to save the system information to a .txt file and send the file to our tech support with other e-mail application. Go to the following web <http://www.biostar.com.tw/app/en-us/about/contact.php> for getting our contact information.


BIOS Update

BIOS Update is a convenient utility which allows you to update your motherboard BIOS under Windows system.



<Backup BIOS>

Once click on this button, the saving dialog will show. Choose the position to save file and enter file name. (We recommend that the file name should be English/number and no longer than 7 characters.) Then click **Save**.





After the saving process, finish dialog will show. Click on **OK** to complete the BIOS Backup procedure.

<Update BIOS>



Before doing this, please download the proper BIOS file from the website.

For AWARD BIOS, update BIOS procedure should be run with Clear CMOS function, so please check on Clear CMOS first.




Then click Update BIOS button, a dialog will show for asking you backup current BIOS. Click **Yes** for BIOS backup and refer to the Backup BIOS procedure; or click **No** to skip this procedure.


After the BIOS Backup procedure, the open dialog will show for requesting the BIOS file which is going to be updated. Please choose the proper BIOS file for updating, then click on **Open**.



The utility will update BIOS with the proper BIOS file, and this process may take minutes. Please do not open any other applications during this process.

After the BIOS Update process, click on **OK** to restart the system.



While the system boots up and the full screen logo shows, press  <Delete> key to enter BIOS setup.

In the BIOS setup, use the **Load Optimized Defaults** function and then **Save and Exit Setup** to exit BIOS setup. BIOS Update is completed.




All the information and content above about the T-Series software are subject to be changed without notice. For better performance, the software is being continuously updated. The information and pictures described above are for your reference only. The actual information and settings on board may be slightly different from this manual.

CHAPTER 5: USEFUL HELP

5.1 DRIVER INSTALLATION NOTE

After you installed your operating system, please insert the Fully Setup Driver CD into your optical drive and install the driver for better system performance.

You will see the following window after you insert the CD



The setup guide will auto detect your motherboard and operating system.

Note:

If this window didn't show up after you insert the Driver CD, please use file browser to locate and execute the file **SETUP.EXE** under your optical drive.

A. Driver Installation

To install the driver, please click on the Driver icon. The setup guide will list the compatible driver for your motherboard and operating system. Click on each device driver to launch the installation program.

B. Software Installation

To install the software, please click on the Software icon. The setup guide will list the software available for your system, click on each software title to launch the installation program.

C. Manual

Aside from the paperback manual, we also provide manual in the Driver CD. Click on the Manual icon to browse for available manual.

Note:

You will need Acrobat Reader to open the manual file. Please download the latest version of Acrobat Reader software from <http://www.adobe.com/products/acrobat/readstep2.html>

5.2 EXTRA INFORMATION

CPU Overheated

If the system shutdown automatically after power on system for seconds, that means the CPU protection function has been activated.

When the CPU is over heated, the motherboard will shutdown automatically to avoid a damage of the CPU, and the system may not power on again.

In this case, please double check:

1. The CPU cooler surface is placed evenly with the CPU surface.
2. CPU fan is rotated normally.
3. CPU fan speed is fulfilling with the CPU speed.

After confirmed, please follow steps below to relief the CPU protection function.

1. Remove the power cord from power supply for seconds.
2. Wait for seconds.
3. Plug in the power cord and boot up the system.

Or you can:

1. Clear the CMOS data.
(See "Close CMOS Header: JCMOS1" section)
2. Wait for seconds.
3. Power on the system again.

5.3 AMI BIOS BEEP CODE

Boot Block Beep Codes

Number of Beeps	Description
1	No media present. (Insert diskette in floppy drive A:)
2	"AMIBOOT.ROM" file not found in root directory of diskette in A:
3	Insert next diskette if multiple diskettes are used for recovery
4	Flash Programming successful
5	File read error
7	No Flash EPROM detected
10	Flash Erase error
11	Flash Program error
12	"AMIBOOT.ROM" file size error
13	BIOS ROM image mismatch (file layout does not match image present in flash device)

POST BIOS Beep Codes

Number of Beeps	Description
1	Memory refresh timer error
3	Base memory read/write test error
6	Keyboard controller BAT command failed
7	General exception error (processor exception interrupt error)
8	Display memory error (system video adapter)

Troubleshooting POST BIOS Beep Codes

Number of Beeps	Troubleshooting Action
1, 3	Reseat the memory, or replace with known good modules.
6, 7	<p>Fatal error indicating a serious problem with the system. Consult your system manufacturer. Before declaring the motherboard beyond all hope, eliminate the possibility of interference by a malfunctioning add-in card. Remove all expansion cards except the video adapter.</p> <ul style="list-style-type: none"> ● If beep codes are generated when all other expansion cards are absent, consult your system manufacturer's technical support. ● If beep codes are not generated when all other expansion cards are absent, one of the add-in cards is causing the malfunction. Insert the cards back into the system one at a time until the problem happens again. This will reveal the malfunctioning card.
8	If the system video adapter is an add-in card, replace or reseat the video adapter. If the video adapter is an integrated part of the system board, the board may be faulty.

5.4 TROUBLESHOOTING

Probable	Solution
1. No power to the system at all Power light don't illuminate, fan inside power supply does not turn on. 2. Indicator light on keyboard does not turn on.	1. Make sure power cable is securely plugged in. 2. Replace cable. 3. Contact technical support.
System inoperative. Keyboard lights are on, power indicator lights are lit, and hard drive is spinning.	Using even pressure on both ends of the DIMM, press down firmly until the module snaps into place.
System does not boot from a hard disk drive, but can be booted from optical drive.	1. Check cable running from disk to disk controller board. Make sure both ends are securely plugged in; check the drive type in the standard CMOS setup. 2. Backing up the hard drive is extremely important. All hard disks are capable of breaking down at any time.
System only boots from an optical drive. Hard disks can be read, applications can be used, but system fails to boot from a hard disk.	1. Back up data and applications files. 2. Reformat the hard drive. Re-install applications and data using backup disks.
Screen message shows "Invalid Configuration" or "CMOS Failure."	Review system's equipment. Make sure correct information is in setup.
System cannot boot after user installs a second hard drive.	1. Set master/slave jumpers correctly. 2. Run SETUP program and select correct drive types. Call the drive manufacturers for compatibility with other drives.

APPENDIX: SPEC IN OTHER LANGUAGES

GERMAN

	<i>TP43E XE/TP43E HP</i>	<i>TP45E HP</i>
CPU	LGA 775 Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Prozessoren Unterstützt Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technology	LGA 775 Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Prozessoren Unterstützt Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technology
FSB	800 / 1066 / 1333 / 1600 MHz	800 / 1066 / 1333 / 1600 MHz
Chipsatz	Intel P43 Intel ICH10	Intel P45 Intel ICH10
Super E/A	ITE 8718F Bietet die häufig verwendeten alten Super E/A-Funktionen. Low Pin Count-Schnittstelle Umgebungskontrolle, Hardware-Überwachung Lüfterdrehzahl-Controller/-Überwachung "Smart Guardian"-Funktion von ITE	ITE 8718F Bietet die häufig verwendeten alten Super E/A-Funktionen. Low Pin Count-Schnittstelle Umgebungskontrolle, Hardware-Überwachung Lüfterdrehzahl-Controller/-Überwachung "Smart Guardian"-Funktion von ITE
Arbeitsspeicher	DDR2 DIMM-Steckplätze x 4 Jeder DIMM unterstützt 256MB / 512MB / 1GB / 2GB / 4GB DDR2. Max. 16GB Arbeitsspeicher Dual-Kanal DDR2 Speichermodul Unterstützt DDR2 1200 (OC) / 1066 / 800 / 667 registrierte DIMMs. ECC DIMMs werden nicht unterstützt.	DDR2 DIMM-Steckplätze x 4 Jeder DIMM unterstützt 256MB / 512MB / 1GB / 2GB / 4GB DDR2. Max. 16GB Arbeitsspeicher Dual-Kanal DDR2 Speichermodul Unterstützt DDR2 1200 (OC) / 1066 / 800 / 667 registrierte DIMMs. ECC DIMMs werden nicht unterstützt.
IDE	JMicro JMB368 Ultra DMA 33 / 66 / 100 / 133 Bus Master-Modus Unterstützt PIO-Modus 0~4,	JMicro JMB368 Ultra DMA 33 / 66 / 100 / 133 Bus Master-Modus Unterstützt PIO-Modus 0~4,
SATA	Integrierter Serial ATA-Controller Datenferrate bis zu 3.0Gb/s Konform mit der SATA-Spezifikation Version 2.0.	Integrierter Serial ATA-Controller Datenferrate bis zu 3.0Gb/s Konform mit der SATA-Spezifikation Version 2.0.
LAN	Realtek RTL 8111DL 10 / 100 / 1000 Mb/s Auto-Negotiation Halb-/ Voll duplex-Funktion	Realtek RTL 8111DL 10 / 100 / 1000 Mb/s Auto-Negotiation Halb-/ Voll duplex-Funktion

TP43E XE/TP43E HP/TP45E HP

	TP43E XE/TP43E HP	TP45E HP
HD	ALC888	ALC888
Audio-Unterstützung	Unterstützt High-Definition Audio 7.1-Kanal-Audioausgabe	Unterstützt High-Definition Audio 7.1-Kanal-Audioausgabe
Steckplätze	PCI-Steckplatz x3	PCI-Steckplatz x3
	PCI Express Gen2 x16 Steckplatz x1	PCI Express Gen2 x16 Steckplatz x1
	PCI Express x 1-Steckplatz x2	PCI Express x 1-Steckplatz x2
Onboard-Anschluss	Diskettenlaufwerkanschluss x1	Diskettenlaufwerkanschluss x1
	IDE-Anschluss x1	IDE-Anschluss x1
	SATA-Anschluss x6	SATA-Anschluss x6
	Fronttafelanschluss x1	Fronttafelanschluss x1
	Front-Audioanschluss x1	Front-Audioanschluss x1
	CD-IN-Anschluss x1	CD-IN-Anschluss x1
	CPU-Lüfter-Sockel x1	CPU-Lüfter-Sockel x1
	System-Lüfter-Sockel x2	System-Lüfter-Sockel x2
	"CMOS löschen"-Sockel x1	"CMOS löschen"-Sockel x1
	USB-Anschluss x3	USB-Anschluss x3
Rückseiten-E/A	Stromanschluss (24-polig) x1	Stromanschluss (24-polig) x1
	Stromanschluss (4-polig) x2	Stromanschluss (4-polig) x2
	PS/2-Tastatur x1	PS/2-Tastatur x1
	PS/2-Maus x1	PS/2-Maus x1
	LAN-Anschluss x1	LAN-Anschluss x1
Platinengröße	USB-Anschluss x6	USB-Anschluss x6
	Audioanschluss x6	Audioanschluss x6
OS-Unterstützung	Optisches +coaxial S/PDIF heraus x1	Optisches +coaxial S/PDIF heraus x1
	220 mm (B) X 305 mm (L)	220 mm (B) X 305 mm (L)
	Windows XP / VISTA 32 / VISTA 64 Biostar behält sich das Recht vor, ohne Ankündigung die Unterstützung für ein Betriebssystem hinzuzufügen oder zu entfernen.	Windows XP / VISTA 32 / VISTA 64 Biostar behält sich das Recht vor, ohne Ankündigung die Unterstützung für ein Betriebssystem hinzuzufügen oder zu entfernen.

FRENCH

	TP43E XE/TP43E HP	TP43 XE
UC	LGA 775 Processeurs Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Prend en charge les technologies d'exécution de bit de désactivation / Intel SpeedStep® optimisée/ d'architecture Intel 64 / de mémoire étendue 64 / de virtualisation	LGA 775 Processeurs Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Prend en charge les technologies d'exécution de bit de désactivation / Intel SpeedStep® optimisée/ d'architecture Intel 64 / de mémoire étendue 64 / de virtualisation
Bus frontal	800 / 1066 / 1333 / 1600 MHz	800 / 1066 / 1333 / 1600 MHz
Chipset	Intel P43 Intel ICH10	Intel P45 Intel ICH10
Super E/S	ITE 8718F Fournit la fonctionnalité de Super E/S patrimoniales la plus utilisée. Interface à faible compte de broches Initiatives de contrôle environnementales, Moniteur de matériel Contrôleur /moniteur de vitesse de ventilateur Fonction "Gardien intelligent" de l'ITE	ITE 8718F Fournit la fonctionnalité de Super E/S patrimoniales la plus utilisée. Interface à faible compte de broches Initiatives de contrôle environnementales, Moniteur de matériel Contrôleur /moniteur de vitesse de ventilateur Fonction "Gardien intelligent" de l'ITE
Mémoire principale	Fentes DDR2 DIMM x 4 Chaque DIMM prend en charge des DDR2 de 256Mo / 512Mo / 1Go / 2Go / 4Go Capacité mémoire maximale de 16Go Module de mémoire DDR2 à mode à double voie Prend en charge la DDR2 1200 (OC) / 1066 / 800 / 667 Les DIMM à registres et DIMM avec code correcteurs d'erreurs ne sont pas prises en charge	Fentes DDR2 DIMM x 4 Chaque DIMM prend en charge des DDR2 de 256Mo / 512Mo / 1Go / 2Go / 4Go Capacité mémoire maximale de 16Go Module de mémoire DDR2 à mode à double voie Prend en charge la DDR2 1200 (OC) / 1066 / 800 / 667 Les DIMM à registres et DIMM avec code correcteurs d'erreurs ne sont pas prises en charge
IDE	JMicro JMB368 Mode principale de Bus Ultra DMA 33 / 66 / 100 / 133 Prend en charge le mode PIO 0~4,	JMicro JMB368 Mode principale de Bus Ultra DMA 33 / 66 / 100 / 133 Prend en charge le mode PIO 0~4,
SATA	Contrôleur Serial ATA intégré : Taux de transfert jusqu'à 3.0Go/s. Conforme à la spécification SATA Version 2.0	Contrôleur Serial ATA intégré : Taux de transfert jusqu'à 3.0Go/s. Conforme à la spécification SATA Version 2.0

TP43E XE/TP43E HP/TP45E HP

	TP43E XE/TP43E HP	TP43 XE
LAN	Realtek RTL 8111DL 10 / 100 / 1000 Mb/s négociation automatique Half / Full duplex capability	Realtek RTL 8111DL 10 / 100 / 1000 Mb/s négociation automatique Half / Full duplex capability
Prise en charge audio HD	ALC888 Prise en charge de l'audio haute définition Sortie audio à 7.1 voies	ALC888 Prise en charge de l'audio haute définition Sortie audio à 7.1 voies
Fentes	Fente PCI x3 Fente PCI Express Gen2 x16 x1 Fente PCI Express x1 x2	Fente PCI x3 Fente PCI Express Gen2 x16 x1 Fente PCI Express x1 x2
Connecteur embarqué	Connecteur de disquette x1 Connecteur IDE x1 Connecteur SATA x6 Connecteur du panneau avant x1 Connecteur Audio du panneau avant x1 Connecteur d'entrée CD x1 Embase de ventilateur UC x1 Embase de ventilateur système x2 Embase d'effacement CMOS x1 Connecteur USB x3 Connecteur d'alimentation (24 broches) x1 Connecteur d'alimentation (4 broches) x2	Connecteur de disquette x1 Connecteur IDE x1 Connecteur SATA x6 Connecteur du panneau avant x1 Connecteur Audio du panneau avant x1 Connecteur d'entrée CD x1 Embase de ventilateur UC x1 Embase de ventilateur système x2 Embase d'effacement CMOS x1 Connecteur USB x3 Connecteur d'alimentation (24 broches) x1 Connecteur d'alimentation (4 broches) x2
E/S du panneau arrière	Clavier PS/2 x1 Souris PS/2 x1 Port LAN x1 Port USB x6 Fiche audio x6 +coaxial optique sortie S/PDIF x1	Clavier PS/2 x1 Souris PS/2 x1 Port LAN x1 Port USB x6 Fiche audio x6 +coaxial optique sortie S/PDIF x1
Dimensions de la carte	220 mm (l) X 305 mm (H)	220 mm (l) X 305 mm (H)
Support SE	Windows XP / VISTA 32 / VISTA 64 Biostar se réserve le droit d'ajouter ou de supprimer le support de SE avec ou sans préavis.	Windows XP / VISTA 32 / VISTA 64 Biostar se réserve le droit d'ajouter ou de supprimer le support de SE avec ou sans préavis.

ITALIAN

	<i>TP43E XE/TP43E HP</i>	<i>TP43 XE</i>
CPU	LGA 775 Processore Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Supporto di Execute Disable Bit / Enhanced Intel SpeedStep® / Architettura Intel 64 / Tecnologia Extended Memory 64 / Tecnologia Virtualization	LGA 775 Processore Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Supporto di Execute Disable Bit / Enhanced Intel SpeedStep® / Architettura Intel 64 / Tecnologia Extended Memory 64 / Tecnologia Virtualization
FSB	800 / 1066 / 1333 / 1600 MHz	800 / 1066 / 1333 / 1600 MHz
Chipset	Intel P43 Intel ICH10	Intel P45 Intel ICH10
Super I/O	ITE 8718F Fornisce le funzionalità legacy Super I/O usate più comunemente. Interfaccia LPC (Low Pin Count) Funzioni di controllo dell'ambiente: Monitoraggio hardware Controller / Monitoraggio velocità ventolina Funzione "Smart Guardian" di ITE	ITE 8718F Fornisce le funzionalità legacy Super I/O usate più comunemente. Interfaccia LPC (Low Pin Count) Funzioni di controllo dell'ambiente: Monitoraggio hardware Controller / Monitoraggio velocità ventolina Funzione "Smart Guardian" di ITE
Memoria principale	Alloggi DIMM DDR2 x 4 Ciascun DIMM supporta DDR2 256MB / 512MB / 1GB / 2GB / 4GB Capacità massima della memoria 16GB Modulo di memoria DDR2 a canale doppio Supporto di DDR2 1200 (OC) / 1066 / 800 / 667 DIMM registrati e DIMM ECC non sono supportati	Alloggi DIMM DDR2 x 4 Ciascun DIMM supporta DDR2 256MB / 512MB / 1GB / 2GB / 4GB Capacità massima della memoria 16GB Modulo di memoria DDR2 a canale doppio Supporto di DDR2 1200 (OC) / 1066 / 800 / 667 DIMM registrati e DIMM ECC non sono supportati
IDE	JMicro JMB368 Modalità Bus Master Ultra DMA 33 / 66 / 100 / 133 Supporto modalità PIO Mode 0-4	JMicro JMB368 Modalità Bus Master Ultra DMA 33 / 66 / 100 / 133 Supporto modalità PIO Mode 0-4
SATA	Controller Serial ATA integrato Velocità di trasferimento dei dati fino a 3.0Gb/s. Compatibile specifiche SATA Versione 2.0.	Controller Serial ATA integrato Velocità di trasferimento dei dati fino a 3.0Gb/s. Compatibile specifiche SATA Versione 2.0.
LAN	Realtek RTL 8111DL Negoziazione automatica 10 / 100 / 1000 Mb/s Capacità Half / Full Duplex	Realtek RTL 8111DL Negoziazione automatica 10 / 100 / 1000 Mb/s Capacità Half / Full Duplex

TP43E XE/TP43E HP/TP45E HP

	TP43E XE/TP43E HP	TP43 XE
Supporto audio HD	ALC888 Supporto audio High-Definition (HD) Uscita audio 7.1 canali	ALC888 Supporto audio High-Definition (HD) Uscita audio 7.1 canali
Alloggi	Alloggio PCI x3 Alloggio PCI Express Gen2 x16 x1 Alloggio PCI Express x1 x2	Alloggio PCI x3 Alloggio PCI Express Gen2 x16 x1 Alloggio PCI Express x1 x2
Connettori su scheda	Connettore floppy x1 Connettore IDE x1 Connettore SATA x6 Connettore pannello frontale x1 Connettore audio frontale x1 Connettore CD-in x1 Collettore ventolina CPU x1 Collettore ventolina sistema x2 Collettore cancellazione CMOS x1 Connettore USB x3 Connettore alimentazione (24 pin) x1 Connettore alimentazione (4 pin) x2	Connettore floppy x1 Connettore IDE x1 Connettore SATA x6 Connettore pannello frontale x1 Connettore audio frontale x1 Connettore CD-in x1 Collettore ventolina CPU x1 Collettore ventolina sistema x2 Collettore cancellazione CMOS x1 Connettore USB x3 Connettore alimentazione (24 pin) x1 Connettore alimentazione (4 pin) x2
I/O pannello posteriore	Tastiera PS/2 x1 Mouse PS/2 x1 Porta LAN x1 Porta USB x6 Connettore audio x6 +coaxial ottico S/PDIF fuori x1	Tastiera PS/2 x1 Mouse PS/2 x1 Porta LAN x1 Porta USB x6 Connettore audio x6 +coaxial ottico S/PDIF fuori x1
Dimensioni scheda	220 mm (larghezza) x 305 mm (altezza)	220 mm (larghezza) x 305 mm (altezza)
Sistemi operativi supportati	Windows XP / VISTA 32 / VISTA 64 Biostar si riserva il diritto di aggiungere o rimuovere il supporto di qualsiasi sistema operativo senza preavviso.	Windows XP / VISTA 32 / VISTA 64 Biostar si riserva il diritto di aggiungere o rimuovere il supporto di qualsiasi sistema operativo senza preavviso.

SPANISH

	TP43E XE/TP43E HP	TP45E HP
CPU	LGA 775 Procesador Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Admite Bit de deshabilitación de ejecución / Intel SpeedStep® Mejorado / Intel Architecture-64 / Tecnología Extended Memory 64 / Tecnología de virtualización	LGA 775 Procesador Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Admite Bit de deshabilitación de ejecución / Intel SpeedStep® Mejorado / Intel Architecture-64 / Tecnología Extended Memory 64 / Tecnología de virtualización
FSB	800 / 1066 / 1333 / 1600 MHz	800 / 1066 / 1333 / 1600 MHz
Conjunto de chips	Intel P43 Intel ICH10	Intel P45 Intel ICH10
Súper E/S	ITE 8718F Le ofrece las funcionalidades heredadas de uso más común Súper E/S. Interfaz de cuenta Low Pin Iniciativas de control de entorno, Monitor hardware Controlador/monitor de velocidad de ventilador Función "Guardia inteligente" de ITE	ITE 8718F Le ofrece las funcionalidades heredadas de uso más común Súper E/S. Interfaz de cuenta Low Pin Iniciativas de control de entorno, Monitor hardware Controlador/monitor de velocidad de ventilador Función "Guardia inteligente" de ITE
Memoria principal	Ranuras DIMM DDR2 x 4 Cada DIMM admite DDR de 256MB / 512MB / 1GB / 2GB / 4GB Capacidad máxima de memoria de 16GB Módulo de memoria DDR2 de canal Doble Admite DDR2 de 1200 (OC) / 1066 / 800 / 667 No admite DIMM registrados o DIMM compatibles con ECC	Ranuras DIMM DDR2 x 4 Cada DIMM admite DDR de 256MB / 512MB / 1GB / 2GB / 4GB Capacidad máxima de memoria de 16GB Módulo de memoria DDR2 de canal Doble Admite DDR2 de 1200 (OC) / 1066 / 800 / 667 No admite DIMM registrados o DIMM compatibles con ECC
IDE	JMicro JMB368 Modo bus maestro Ultra DMA 33 / 66 / 100 / 133 Soporte los Modos PIO 0~4,	JMicro JMB368 Modo bus maestro Ultra DMA 33 / 66 / 100 / 133 Soporte los Modos PIO 0~4,
SATA	Controlador ATA Serie Integrado Tasas de transferencia de hasta 3.0 Gb/s. Compatible con la versión SATA 2.0.	Controlador ATA Serie Integrado Tasas de transferencia de hasta 3.0 Gb/s. Compatible con la versión SATA 2.0.
Red Local	Realtek RTL 8111DL Negociación de 10 / 100 / 1000 Mb/s Funciones Half / Full dúplex	Realtek RTL 8111DL Negociación de 10 / 100 / 1000 Mb/s Funciones Half / Full dúplex

TP43E XE/TP43E HP/TP45E HP

	TP43E XE/TP43E HP	TP45E HP
Sopte de sonido HD	ALC888 Soporte de sonido de Alta Definición Salida de sonido de 7.1 canales	ALC888 Soporte de sonido de Alta Definición Salida de sonido de 7.1 canales
Ranuras	Ranura PCI X3 Ranura PCI Express Gen2 x16 X1 Ranura PCI express x 1 X2	Ranura PCI X3 Ranura PCI Express Gen2 x16 X1 Ranura PCI express x 1 X2
Conectores en placa	Conector disco flexible X1 Conector IDE X1 Conector SATA X6 Conector de panel frontal X1 Conector de sonido frontal X1 Conector de entrada de CD X1 Cabecera de ventilador de CPU X1 Cabecera de ventilador de sistema X2 Cabecera de borrado de CMOS X1 Conector USB X3 Conector de alimentación (24 patillas) X1 Conector de alimentación (4 patillas) X2	Conector disco flexible X1 Conector IDE X1 Conector SATA X6 Conector de panel frontal X1 Conector de sonido frontal X1 Conector de entrada de CD X1 Cabecera de ventilador de CPU X1 Cabecera de ventilador de sistema X2 Cabecera de borrado de CMOS X1 Conector USB X3 Conector de alimentación (24 patillas) X1 Conector de alimentación (4 patillas) X2
Panel trasero de E/S	Teclado PS/2 X1 Ratón PS/2 X1 Puerto de red local X1 Puerto USB X6 Conector de sonido X6 +coaxial óptico salida S/PDIF x1	Teclado PS/2 X1 Ratón PS/2 X1 Puerto de red local X1 Puerto USB X6 Conector de sonido X6 +coaxial óptico salida S/PDIF x1
Tamaño de la placa	220 mm. (A) X 305 Mm. (H)	220 mm. (A) X 305 Mm. (H)
Sopte de sistema operativo	Windows XP / VISTA 32 / VISTA 64 Biostar se reserva el derecho de añadir o retirar el soporte de cualquier SO con o sin aviso previo.	Windows XP / VISTA 32 / VISTA 64 Biostar se reserva el derecho de añadir o retirar el soporte de cualquier SO con o sin aviso previo.

PORTUGUESE

	TP43E XE/TP43E HP	TP45E HP
CPU	LGA 775 Processador Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Suporta as tecnologias Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture -64 / Extended Memory 64 / Virtualization	LGA 775 Processador Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Suporta as tecnologias Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture -64 / Extended Memory 64 / Virtualization
FSB	800 / 1066 / 1333 / 1600 MHz	800 / 1066 / 1333 / 1600 MHz
Chipset	Intel P43 Intel ICH10	Intel P45 Intel ICH10
Especificação do Super I/O	ITE 8718F Proporciona as funcionalidades mais utilizadas em termos da especificação Super I/O. Interface LPC (Low Pin Count). Iniciativas para controlo do ambiente Monitorização do hardware Controlador/Monitor da velocidade da ventoinha Função "Smart Guardian" da ITE	ITE 8718F Proporciona as funcionalidades mais utilizadas em termos da especificação Super I/O. Interface LPC (Low Pin Count). Iniciativas para controlo do ambiente Monitorização do hardware Controlador/Monitor da velocidade da ventoinha Função "Smart Guardian" da ITE
Memória principal	Ranuras DIMM DDR2 x 4 Cada módulo DIMM suporta uma memória DDR2 de 256 MB / 512 MB / 1GB / 2GB / 4GB Capacidade máxima de memória:16 GB Módulo de memória DDR2 de canal duplo Suporta módulos DDR2 1200 (OC) / 1066 / 800 / 667 Os módulos DIMM registados e os DIMM ECC não são suportados	Ranuras DIMM DDR2 x 4 Cada módulo DIMM suporta uma memória DDR2 de 256 MB / 512 MB / 1GB / 2GB / 4GB Capacidade máxima de memória:16 GB Módulo de memória DDR2 de canal duplo Suporta módulos DDR2 1200 (OC) / 1066 / 800 / 667 Os módulos DIMM registados e os DIMM ECC não são suportados
IDE	JMicro JMB368 Modo Bus master Ultra DMA 33 / 66 / 100 / 133 Suporta o modo PIO 0~4,	JMicro JMB368 Modo Bus master Ultra DMA 33 / 66 / 100 / 133 Suporta o modo PIO 0~4,
SATA	Controlador Serial ATA integrado Velocidades de transmissão de dados até 3.0 Gb/s. Compatibilidade com a especificação SATA versão 2.0.	Controlador Serial ATA integrado Velocidades de transmissão de dados até 3.0 Gb/s. Compatibilidade com a especificação SATA versão 2.0.
LAN	Realtek RTL 8111DL Auto negociação de 10 / 100 / 1000 Mb/s Capacidade semi/full-duplex	Realtek RTL 8111DL Auto negociação de 10 / 100 / 1000 Mb/s Capacidade semi/full-duplex

TP43E XE/TP43E HP/TP45E HP

	TP43E XE/TP43E HP		TP45E HP	
Suporte para áudio de alta definição	ALC888		ALC888	
	Suporta a especificação High-Definition Audio		Suporta a especificação High-Definition Audio	
	Saída de áudio de 7.1 canais		Saída de áudio de 7.1 canais	
Ranhuras	Ranhura PCI	x3	Ranhura PCI	x3
	Ranhura PCI Express Gen2 x16	x1	Ranhura PCI Express Gen2 x16	x1
	Ranhura PCI Express x 1	x2	Ranhura PCI Express x 1	x2
Conectores na placa	Conector da unidade de disquetes	x1	Conector da unidade de disquetes	x1
	Conector IDE	x1	Conector IDE	x1
	Conector SATA	x6	Conector SATA	x6
	Conector do painel frontal	x1	Conector do painel frontal	x1
	Conector de áudio frontal	x1	Conector de áudio frontal	x1
	Conector para entrada de CDs	x1	Conector para entrada de CDs	x1
	Conector da ventoinha da CPU	x1	Conector da ventoinha da CPU	x1
	Conector da ventoinha do sistema	x2	Conector da ventoinha do sistema	x2
	Conector para limpeza do CMOS	x1	Conector para limpeza do CMOS	x1
	Conector USB	x3	Conector USB	x3
	Conector de alimentação (24 pinos)	x1	Conector de alimentação (24 pinos)	x1
	Conector de alimentação (4 pinos)	x2	Conector de alimentação (4 pinos)	x2
Entradas/Saídas no painel traseiro	Teclado PS/2	x1	Teclado PS/2	x1
	Rato PS/2	x1	Rato PS/2	x1
	Porta LAN	x1	Porta LAN	x1
	Porta USB	x6	Porta USB	x6
	Tomada de áudio	x6	Tomada de áudio	x6
	+coaxial ótico saída S/PDIF	x1	+coaxial ótico saída S/PDIF	x1
Tamanho da placa	220 mm (L) X 305 mm (A)		220 mm (L) X 305 mm (A)	
Sistemas operativos suportados	Windows XP / VISTA 32 / VISTA 64 A Biostar reserva-se o direito de adicionar ou remover suporte para qualquer sistema operativo com ou sem aviso prévio.		Windows XP / VISTA 32 / VISTA 64 A Biostar reserva-se o direito de adicionar ou remover suporte para qualquer sistema operativo com ou sem aviso prévio.	

POLISH

	TP43E XE/TP43E HP	TP45E HP
Procesor	LGA 775 Procesor Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Obsługa Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technology	LGA 775 Procesor Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Obsługa Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technology
FSB	800 / 1066 / 1333 / 1600 MHz	800 / 1066 / 1333 / 1600 MHz
Chipset	Intel P43 Intel ICH10	Intel P45 Intel ICH10
Pamięć główna	Gniazda DDR2 DIMM x 4 Każde gniazdo DIMM obsługuje moduły 256MB / 512MB / 1GB / 2GB / 4GB Maks. wielkość pamięci 16GB Moduł pamięci DDR2 z trybem podwójnego kanału Obsługa DDR2 1200 (OC) / 1066 / 800 / 667 Brak obsługi Registered DIMM oraz ECC DIMM	Gniazda DDR2 DIMM x 4 Każde gniazdo DIMM obsługuje moduły 256MB / 512MB / 1GB / 2GB / 4GB Maks. wielkość pamięci 16GB Moduł pamięci DDR2 z trybem podwójnego kanału Obsługa DDR2 1200 (OC) / 1066 / 800 / 667 Brak obsługi Registered DIMM oraz ECC DIMM
Super I/O	ITE 8718F Zapewnia najbardziej powszechne funkcje Super I/O. Interfejs Low Pin Count Funkcje kontroli warunków pracy, Monitor H/W Kontroler/Monitor prędkości wentylatora Funkcja ITE "Smart Guardian"	ITE 8718F Zapewnia najbardziej powszechne funkcje Super I/O. Interfejs Low Pin Count Funkcje kontroli warunków pracy, Monitor H/W Kontroler/Monitor prędkości wentylatora Funkcja ITE "Smart Guardian"
IDE	JMicro JMB368 Ultra DMA 33 / 66 / 100 / 133 Tryb Bus Master obsługa PIO tryb 0~4,	JMicro JMB368 Ultra DMA 33 / 66 / 100 / 133 Tryb Bus Master obsługa PIO tryb 0~4,
SATA	Zintegrowany kontroler Serial ATA Transfer danych do 3.0 Gb/s. Zgodność ze specyfikacją SATA w wersji 2.0.	Zintegrowany kontroler Serial ATA Transfer danych do 3.0 Gb/s. Zgodność ze specyfikacją SATA w wersji 2.0.
LAN	Realtek RTL 8111DL 10 / 100 / 1000 Mb/s z automatyczną negocjacją szybkości Działanie w trybie półwicznego / pełnego dupleksu	Realtek RTL 8111DL 10 / 100 / 1000 Mb/s z automatyczną negocjacją szybkości Działanie w trybie półwicznego / pełnego dupleksu
Obsługa audio HD	ALC888 Obsługa High-Definition Audio 7.1 kanałowe wyjście audio	ALC888 Obsługa High-Definition Audio 7.1 kanałowe wyjście audio

TP43E XE/TP43E HP/TP45E HP

		TP43E XE/TP43E HP	TP45E HP
Gniazda	Gniazdo PCI	x3	Gniazdo PCI x3
	Gniazdo PCI Express Gen2 x16	x1	Gniazdo PCI Express Gen2 x16 x1
	Gniazdo PCI Express x 1	x2	Gniazdo PCI Express x 1 x2
Złącza wbudowane	Złącze napędu dyskietek	x1	Złącze napędu dyskietek x1
	Złącze IDE	x1	Złącze IDE x1
	Złącze SATA	x6	Złącze SATA x6
	Złącze panela przedniego	x1	Złącze panela przedniego x1
	Przednie złącze audio	x1	Przednie złącze audio x1
	Złącze wejścia CD	x1	Złącze wejścia CD x1
	Złącze głośnikowe wentylatora procesora	x1	Złącze głośnikowe wentylatora procesora x1
	Złącze głośnikowe wentylatora systemowego	x2	Złącze głośnikowe wentylatora systemowego x2
	Złącze głośnikowe kasowania CMOS	x1	Złącze głośnikowe kasowania CMOS x1
	Złącze USB	x3	Złącze USB x3
Złącze zasilania (24 pinowe)	x1	Złącze zasilania (24 pinowe) x1	
Złącze zasilania (4 pinowe)	x2	Złącze zasilania (4 pinowe) x2	
Back Panel I/O	Klawiatura PS/2	x1	Klawiatura PS/2 x1
	Mysz PS/2	x1	Mysz PS/2 x1
	Port LAN	x1	Port LAN x1
	Port USB	x6	Port USB x6
	Gniazdo audio	x6	Gniazdo audio x6
	Optyczny +coaxial wyjścia S/PDIF	x1	Optyczny +coaxial wyjścia S/PDIF x1
Wymiary płyty	220 mm (S) X 305 mm (W)		220 mm (S) X 305 mm (W)
Obsługa systemu operacyjnego	Windows XP / VISTA 32 / VISTA 64 Biostar zastrzega sobie prawo dodawania lub odwoływania obsługi dowolnego systemu operacyjnego bez powiadomienia.		Windows XP / VISTA 32 / VISTA 64 Biostar zastrzega sobie prawo dodawania lub odwoływania obsługi dowolnego systemu operacyjnego bez powiadomienia.

RUSSIAN

	<i>TP43E XE/TP43E HP</i>	<i>TP45E HP</i>
CPU (центральный процессор)	LGA 775 Процессор Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Поддержка технологий Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / технологии виртуализация	LGA 775 Процессор Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx Поддержка технологий Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / технологии виртуализация
FSB	800 / 1066 / 1333 / 1600 МГц	800 / 1066 / 1333 / 1600 МГц
Набор микросхем	Intel P43 Intel ICH10	Intel P45 Intel ICH10
Основная память	Слоты DDR2 DIMM x 4 Каждый модуль DIMM поддерживает 256 МБ / 512МБ / 1ГБ / 2ГБ / 4ГБ DDR2 Максимальная ёмкость памяти 8ГБ Модуль памяти с двухканальным режимом DDR2 Поддержка DDR2 1200 (OC) / 1066 / 800 / 667 Не поддерживает зарегистрированные модули DIMM and ECC DIMM	Слоты DDR2 DIMM x 4 Каждый модуль DIMM поддерживает 256 МБ / 512МБ / 1ГБ / 2ГБ / 4ГБ DDR2 Максимальная ёмкость памяти 8ГБ Модуль памяти с двухканальным режимом DDR2 Поддержка DDR2 1200 (OC) / 1066 / 800 / 667 Не поддерживает зарегистрированные модули DIMM and ECC DIMM
Super I/O	ITE 8718F Обеспечивает наиболее используемые действующие функциональные возможности Super I/O. Интерфейс с низким количеством выводов Инициативы по охране окружающей среды, Аппаратный монитор Регулятор скорости вентилятора/ монитор Функция ITE "Smart Guardian" (Интеллектуальная защита)	ITE 8718F Обеспечивает наиболее используемые действующие функциональные возможности Super I/O. Интерфейс с низким количеством выводов Инициативы по охране окружающей среды, Аппаратный монитор Регулятор скорости вентилятора/ монитор Функция ITE "Smart Guardian" (Интеллектуальная защита)
IDE	JMicro JMB368 Режим "хозяина" шины Ultra DMA 33 / 66 / 100 / 133 Поддержка режима PIO 0~4,	JMicro JMB368 Режим "хозяина" шины Ultra DMA 33 / 66 / 100 / 133 Поддержка режима PIO 0~4,
SATA	Встроенное последовательное устройство управления ATA скорость передачи данных до 3.0 гигабит/с. Соответствие спецификации SATA версия 2.0.	Встроенное последовательное устройство управления ATA скорость передачи данных до 3.0 гигабит/с. Соответствие спецификации SATA версия 2.0.
Локальная сеть	Realtek RTL 8111DL Автоматическое согласование 10 / 100 / 1000 Мб/с Частичная / полная дуплексная способность	Realtek RTL 8111DL Автоматическое согласование 10 / 100 / 1000 Мб/с Частичная / полная дуплексная способность

TP43E XE/TP43E HP/TP45E HP

	TP43E XE/TP43E HP		TP45E HP	
Звуковая поддержка жесткого диска	ALC888 Звуковая поддержка High-Definition 7.1канальный звуковой выход		ALC888 Звуковая поддержка High-Definition 7.1канальный звуковой выход	
Слоты	Слот PCI	x3	Слот PCI	x3
	Слот PCI Express Gen2 x16	x1	Слот PCI Express Gen2 x16	x1
	Слот PCI Express x 1	x2	Слот PCI Express x 1	x2
Встроенный разъем	Разъем НГМД	x1	Разъем НГМД	x1
	Разъем IDE	x1	Разъем IDE	x1
	Разъем SATA	x6	Разъем SATA	x6
	Разъем на лицевой панели	x1	Разъем на лицевой панели	x1
	Входной звуковой разъем	x1	Входной звуковой разъем	x1
	Разъем ввода для CD	x1	Разъем ввода для CD	x1
	Контактирующее приспособление вентилятора центрального процессора	x1	Контактирующее приспособление вентилятора центрального процессора	x1
	Контактирующее приспособление вентилятора системы	x2	Контактирующее приспособление вентилятора системы	x2
	Открытое контактирующее приспособление CMOS	x1	Открытое контактирующее приспособление CMOS	x1
	USB-разъем	x3	USB-разъем	x3
	Разъем питания (24 вывод)	x1	Разъем питания (24 вывод)	x1
	Разъем питания (4 вывод)	x2	Разъем питания (4 вывод)	x2
Задняя панель средств ввода-вывода	Клавиатура PS/2	x1	Клавиатура PS/2	x1
	Мышь PS/2	x1	Мышь PS/2	x1
	Порт LAN	x1	Порт LAN	x1
	USB-порт	x6	USB-порт	x6
	Гнездо для подключения наушников	x6	Гнездо для подключения наушников	x6
	Оптически +coaxial вывода для S/PDIF	x1	Оптически +coaxial вывода для S/PDIF	x1
Размер панели	220 мм (Ш) X 305 мм (В)		220 мм (Ш) X 305 мм (В)	
Поддержка OS	Windows XP / VISTA 32 / VISTA 64 Biostar сохраняет за собой право добавлять или удалять средства обеспечения для OS с или без предварительного уведомления.		Windows XP / VISTA 32 / VISTA 64 Biostar сохраняет за собой право добавлять или удалять средства обеспечения для OS с или без предварительного уведомления.	

ARABIC

TP45E HP	TP43E XE/TP43E HP	
LGA 775 Intel Core2 Extreme / Core2 Duo / Core2 Quad /Pentium Dual-Core / Celeron Dual-Core /Celeron 4xx إلى ٦٦٦ Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technology	LGA 775 Intel Core2 Extreme / Core2 Duo / Core2 Quad /Pentium Dual-Core / Celeron Dual-Core /Celeron 4xx إلى ٦٦٦ Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technology	وحدة المعالجة المركزية
ميجا هرتز 800 / 1066 / 1333 / 1600 تردد	ميجا هرتز 800 / 1066 / 1333 / 1600 تردد	النقل الأمامي الجانبي
Intel P43 Intel ICH10	Intel P45 Intel ICH10	مجموعة الشرائح
عدد4 قناة DDR2 DIMM ميجا 256/512 سعة DDR2 تدعم ذاكرة من نوع DIMM كل قناة غيب/4غيب/2غيب/1 سعة ذاكرة قصوى 16 جيجا بايت مزوجة للقناة DDR2 وحدة ذاكرة تدعم الذاكرة من نوع 2DDR سعت 1200 / 1066 / 800 / 667 (OC) ميجا بايت ECC ونك التي لا تتوافق مع DIMM لا تدعم رقائق الذاكرة	عدد4 قناة DDR2 DIMM ميجا 256/512 سعة DDR2 تدعم ذاكرة من نوع DIMM كل قناة غيب/4غيب/2غيب/1 سعة ذاكرة قصوى 16 جيجا بايت مزوجة للقناة DDR2 وحدة ذاكرة تدعم الذاكرة من نوع 2DDR سعت 1200 / 1066 / 800 / 667 (OC) ميجا بايت ECC ونك التي لا تتوافق مع DIMM لا تدعم رقائق الذاكرة	الذاكرة الرئيسية
ITE 8718F الأكثر استخداماً. Super I/O يوفر وظيفة Low Pin Count Interface تدعم تقنية وسائل التحكم في البيئة: مراقب لمعرفة حالة الأجهزة مراقب في سرعة المروحة ITE من "Smart Guardian" الوظيفة	ITE 8718F الأكثر استخداماً. Super I/O يوفر وظيفة Low Pin Count Interface تدعم تقنية وسائل التحكم في البيئة: مراقب لمعرفة حالة الأجهزة مراقب في سرعة المروحة ITE من "Smart Guardian" وظيفة	Super I/O
JMicro JMB368 IDE متحكم وضع رئيسي 133 / 100 / 66 / 33 Ultra DMA نقل تقنية PIO Mode 0~4 دعم وضع	JMicro JMB368 IDE متحكم وضع رئيسي 133 / 100 / 66 / 33 Ultra DMA نقل تقنية PIO Mode 0~4 دعم وضع	منفذ IDE
متكامل Serial ATA متحكم جيجابت/ثانية 3.0 نقل البيانات بسرعة تصل إلى 2.0 الإصدار SATA مطابقة لمواصفات	متكامل Serial ATA متحكم جيجابت/ثانية 3.0 نقل البيانات بسرعة تصل إلى 2.0 الإصدار SATA مطابقة لمواصفات	SATA
Realtek RTL 8111DL تفاوض تلقائي 100/10 ميجا بايت / ثانية و 1 جيجا بايت/ثانية	Realtek RTL 8111DL تفاوض تلقائي 100/10 ميجا بايت / ثانية و 1 جيجا بايت/ثانية	شبكة داخلية

TP43E XE/TP43E HP/TP45E HP

TP45E HP		TP43E XE/TP43E HP		
إمكانية النقل المزوج الكامل/النصفي		إمكانية النقل المزوج الكامل/النصفي		
ALC888	Intel تدعم تقنية الصوت عالي التعريف من 7.1 قنوات لخرج الصوت	ALC888	تدعم تقنية الصوت عالي التعريف من 7.1 قنوات لخرج الصوت	دعم الصوت عالي التعريف
عدد 3	قناة PCI	عدد 3	قناة PCI	التحات
عدد 1	قناة PCI Express x 16 Gen2	عدد 1	قناة PCI Express x 16 Gen2	
عدد 2	قناة PCI Express x 1	عدد 2	قناة PCI Express x 1	
عدد 1	منفذ محرك أقراص مرنة	عدد 1	منفذ محرك أقراص مرنة	المنفذ على سطح اللوحة
عدد 1	منفذ IDE	عدد 1	منفذ IDE	
عدد 6	منفذ SATA	عدد 6	منفذ SATA	
عدد 1	منفذ للوحة الأممية	عدد 1	منفذ للوحة الأممية	
عدد 1	منفذ الصوت الأممي	عدد 1	منفذ الصوت الأممي	
عدد 1	منفذ CD-IN	عدد 1	منفذ CD-IN	
عدد 1	وصلة مروحة وحدة المعالجة المركزية	عدد 1	وصلة مروحة وحدة المعالجة المركزية	
عدد 2	وصلة مروحة للنظام	عدد 2	وصلة مروحة للنظام	
عدد 1	وصلة مسح CMOS	عدد 1	وصلة مسح CMOS	
عدد 3	منفذ USB	عدد 3	منفذ USB	
عدد 1	منفذ توصيل الطاقة (24بيوس)	عدد 1	منفذ توصيل الطاقة (24بيوس)	
عدد 2	منفذ توصيل الطاقة (4دبابيس)	عدد 2	منفذ توصيل الطاقة (4دبابيس)	
عدد 1	لوحة مفاتيح PS/2	عدد 1	لوحة مفاتيح PS/2	
عدد 1	ملوس PS/2	عدد 1	ملوس PS/2	
عدد 1	منفذ شبكة اتصال محلية	عدد 1	منفذ شبكة اتصال محلية	
عدد 6	منافذ USB	عدد 6	منافذ USB	
عدد 6	مقيس صوت	عدد 6	مقيس صوت	
عدد 1	محور متحد +بصرية منفذ خرج S/PDIF	عدد 1	محور متحد +بصرية منفذ خرج S/PDIF	
220 مم (عرض) X 305 مم (ارتفاع)		220 مم (عرض) X 305 مم (ارتفاع)		حجم اللوحة
Windows XP / VISTA 32 / VISTA 64 يحفظ Biostar بعضها في إضافة أو إزالة الدعم لأي نظام تشغيل بإخطار أو بدون إخطار .		Windows XP / VISTA 32 / VISTA 64 يحفظ Biostar بعضها في إضافة أو إزالة الدعم لأي نظام تشغيل بإخطار أو بدون إخطار .		دعم أنظمة التشغيل

JAPANESE

	TP43E XE/TP43E HP	TP45E HP
CPU	LGA 775 Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx processor Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technologyをサポートします	LGA 775 Intel Core2 Extreme / Core2 Duo / Core2 Quad / Pentium Dual-Core / Celeron Dual-Core / Celeron 4xx processor Execute Disable Bit / Enhanced Intel SpeedStep® / Intel Architecture-64 / Extended Memory 64 Technology / Virtualization Technologyをサポートします
FSB	800 / 1066 / 1333 / 1600 MHz	800 / 1066 / 1333 / 1600 MHz
チップセット	Intel P43 Intel ICH10	Intel P45 Intel ICH10
メインメモリ	DDR2 DIMMスロット x 4 各DIMMは 256MB / 512MB / 1GB / 2GB / 4GB DDR2をサポート 最大メモリ容量 16GB デュアル チャンネルモードDDR2 メモリモジュール DDR2 1200 (OC) / 1066 / 800 / 667をサポート 登録済みDIMMとECC DIMMはサポートされません	DDR2 DIMMスロット x 4 各DIMMは 256MB / 512MB / 1GB / 2GB / 4GB DDR2をサポート 最大メモリ容量 16GB デュアル チャンネルモードDDR2 メモリモジュール DDR2 1200 (OC) / 1066 / 800 / 667をサポート 登録済みDIMMとECC DIMMはサポートされません
Super I/O	ITE 8718F もつとも一般に使用されるレガシーSuper I/O機能を 採用しています。 低ピンカウントインターフェイス 環境コントロールイニシアチブ、 H/W モニター ファン速度コントローラ/ モニター ITEの「スマートガーディアン」機能	ITE 8718F もつとも一般に使用されるレガシーSuper I/O機能を 採用しています。 低ピンカウントインターフェイス 環境コントロールイニシアチブ、 H/W モニター ファン速度コントローラ/ モニター ITEの「スマートガーディアン」機能
IDE	JMicro JMB368 Ultra DMA 33 / 66 / 100 / 133バスマスタモード PIO Mode 0~4のサポート、	JMicro JMB368 Ultra DMA 33 / 66 / 100 / 133バスマスタモード PIO Mode 0~4のサポート、
SATA	統合シリアルATAコントローラ 最高3.0 Gb/秒のデータ転送速度 SATAバージョン2.0仕様に準拠。	統合シリアルATAコントローラ 最高3.0 Gb/秒のデータ転送速度 SATAバージョン2.0仕様に準拠。
LAN	Realtek RTL 8111DL 10 / 100 / 1000 Mb/秒のオートネゴシエーション 半/全二重機能	Realtek RTL 8111DL 10 / 100 / 1000 Mb/秒のオートネゴシエーション 半/全二重機能

TP43E XE/TP43E HP/TP45E HP

	TP43E XE/TP43E HP		TP45E HP	
HDオーディオのサポート	ALC888 ハイデフィニションオーディオのサポート 7.1 チャンネルオーディオアウト		ALC888 ハイデフィニションオーディオのサポート 7.1 チャンネルオーディオアウト	
スロット	PCIスロット	x3	PCIスロット	x3
	PCI Express x16 Gen2スロット	x1	PCI Express x16 Gen2スロット	x1
	PCI Express x 1スロット	x2	PCI Express x 1スロット	x2
オンボードコネクタ	フロッピーコネクタ	x1	フロッピーコネクタ	x1
	IDEコネクタ	x1	IDEコネクタ	x1
	SATAコネクタ	x6	SATAコネクタ	x6
	フロントパネルコネクタ	x1	フロントパネルコネクタ	x1
	フロントオーディオコネクタ	x1	フロントオーディオコネクタ	x1
	CDインコネクタ	x1	CDインコネクタ	x1
	CPUファンヘッダ	x1	CPUファンヘッダ	x1
	システムファンヘッダ	x2	システムファンヘッダ	x2
	CMOSクリアヘッダ	x1	CMOSクリアヘッダ	x1
	USBコネクタ	x3	USBコネクタ	x3
	電源コネクタ(24ピン)	x1	電源コネクタ(24ピン)	x1
	電源コネクタ(4ピン)	x2	電源コネクタ(4ピン)	x2
背面パネル I/O	PS/2キーボード	x1	PS/2キーボード	x1
	PS/2マウス	x1	PS/2マウス	x1
	LANポート	x1	LANポート	x1
	USBポート	x6	USBポート	x6
	オーディオジャック	x6	オーディオジャック	x6
	光学+coaxial S/PDIFアウト	x1	光学+coaxial S/PDIFアウト	x1
ボードサイズ	220 mm (幅) X 305 mm (高さ)		220 mm (幅) X 305 mm (高さ)	
OSサポート	Windows XP / VISTA 32 / VISTA 64 Biostarは事前のサポートなしにOSサポートを追加または削除する権利を留保します。		Windows XP / VISTA 32 / VISTA 64 Biostarは事前のサポートなしにOSサポートを追加または削除する権利を留保します。	

2009/01/14